



## TJ-4522TN

Titan Industrial  
Label Printer

[www.brother.com.au](http://www.brother.com.au)



Food &  
Beverage



Manufacturing  
& Transport



Warehousing  
& Logistics



Retail

# TJ-4522TN

## Titan Industrial Label Printer



### Key features:

- Simple, robust and reliable direct thermal and thermal transfer technology
- Internal rewriter for optimised efficiency
- Print more than 10,000 labels a day
- 300dpi print resolution
- Max. 305mm/sec print speed
- 8.3cm colour LCD
- High-capacity 600m ribbon for fewer changes
- Supports Software Development Kits (SDK's) and printer command languages, including ZPL2 emulation
- USB, Serial, 10/100Base-TX Wired LAN and WLAN connectivity
- Optional dual Wi-Fi and Bluetooth accessory



### Drop-in, connect and print

From shipping and receiving labels, to product and compliance labels (and everything in between!), it's stress-free and seamless to integrate, without compromising productivity



### Compatible with your existing infrastructure

Take advantage of the suite of connectivity options including USB 2.0, serial, Ethernet, and optional dual Wi-Fi and Bluetooth accessories, and its ability to support Software Development Kits (SDK's) and various printer command languages, including ZPL2 emulation



### A solution built for your business

Customise your machine to meet the demands of your business with the optional dual Wi-Fi and Bluetooth accessory to support your critical workflows



### Reliable, built-in technology

The built-in rewriter optimises efficiency and allows you to multi-task - simply send your labels to print and collect the ready-printed label roll whenever you need to! Utilising thermal technology, high capacity 600m ribbons and crisp 300dpi outputs, you'll save time and money while delivering professional results



### Warranty you can count on

A generous 2-year warranty on hardware and print heads means these mission-critical machines will always be performing at their best



### At your side support

Wherever you are in Australia, Brother offers free product support for the lifetime of your product

## Technical Specifications for the TJ-4522TN

General	
Print Technology	Direct Thermal / Thermal Transfer
Print Resolution	300dpi
Maximum Print Speed	305 mm / second
Maximum Print Width	104mm
Maximum Print Length	11,430mm
Minimum Print Length	5mm
Emulation	FBPL-EZD (TSPL2,EPL2,ZPL2,DPL)
Feed	Yes
Internal Rewinder	Yes
Size	
Weight	18.93kg (without roll)
Dimensions	276mm x 502mm x 412mm (W x D x H)
Control Panel	Colour touch display, 1 status indicator and 6 button navigation
Interface	
USB	<b>Standard:</b> USB Ver.2.0 (Full Speed) (Type B)
Serial	<b>Standard:</b> RS232C (DB9 male)
Wired LAN	<b>Standard:</b> 10/100BASE-TX
USB Host Ports	<b>Standard:</b> USB Type-A <b>Class ID:</b> HID, USB mass-storage device class <b>USB Regulation:</b> 2.0
Bluetooth Profile	<b>PA-WB-001 (Optional):</b> Bluetooth Ver.5.0, SPP (Bluetooth Classic), GATT (Bluetooth Low Energy)
Wi-Fi	<b>PA-WB-001 (Optional):</b> IEEE 802.11 a/b/g/n (a band is 5GHz; b/g/n is 2.4GHz)
WLAN Security	Compliant to IEEE 802.11 a/b/g/n with dual band support Supports Bandwidth in 5GHz 20/40 MHz 802.11n <b>Features:</b> 802.11n HT20 Roaming without data lost in AP cover rage <b>Protocols:</b> IPv4, ARP, ICMP, UDP, TCP, RAW, DHCP Client, DHCP FQDN Option, Unicast DHCP Offer
Memory	
Standard Memory	<b>RAM:</b> 128MB <b>Flash:</b> 512MB (MicroSD Flash memory card reader or Flash memory expansion, up to 32GB)
Power Supply	
Adapter	<b>Internal Supply:</b> 100 - 240 V 50/60Hz <b>Output:</b> 24V/3.75A. 90W
Media Specification	
Types	Generic thermal continuous, black mark, die cut label with gap, fan-fold, notch media, perforated, tag, care label
Wound Type	Outside Wound
Roll Size	<b>Tear Mode:</b> 50mm to Max Print Length <b>Peeler Mode:</b> 12.7mm - 152.4mm Length <b>Cutter Mode:</b> 25.4mm - 1,016mm Length <b>Max Roll Diameter:</b> 203.2mm <b>Core size:</b> 38.1mm - 76.2mm <b>Tear / Peeler Mode:</b> 20mm - 120mm Width <b>Cutter Mode:</b> 20mm - 114mm Width
Roll Width	20mm - 114mm
Ribbon Specification	
Types	Wax, Resin, Semi (Wax/Resin)
Wound Type	Inside or Outside Wound
Ribbon Width	20mm - 114mm
Ribbon Length	600m
Software	
Software Included	<b>Windows:</b> BarTender, BPM (Brother Printer Management Tool), CommTool (Brother Communication Tool), Printer Driver <b>Mac:</b> Printer Driver <b>Linux:</b> Printer Driver
Windows Printer Driver	Windows 11 Windows 10 Windows 8.1 Windows 7 Server 2012 Server 2012R2 Server 2016 Server 2019

Software	
MAC Printer Driver	macOS X 10.11.x macOS 10.12 - 12.0
Linux Printer Driver	Linux Ubuntu V11.04-16.04 Fedora 24 SUSE Linux Enterprise Server 12 CentOS Linux 7.2 Red Hat Enterprise 7.3
Mobile Software Development Kits (SDK's)	Android V5 iOS V9
Windows SDK	Server 2019 Windows 10 and Server 2016 Windows 8.1 and Server 2012 R2 Windows 8 and Server 2012 Windows 7
Android SDK	V5-V10
iOS SDK	V9-V13.2
Supported Command	FBPL-EZD (EPL,ZPL,ZPL2,DPL)
SAP Device Type	SAP_BASIS Release 6.20 - 7.11, except 7.10
Bar Code Symbologies	<b>Linear:</b> Code128UCC, Code128 subsets A,B,C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Standard 2 of 5, Insuatrial 2 of 5, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, EAN13, Code11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS <b>2-dimensional:</b> CODABLOCK F mode, GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417, TLC39
Fonts	8 alpha-numeric bitmap fonts for FBPL Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Environment	
Operating Temperature	0 - 40°C
Operating Humidity	25 - 85% non-condensing
Storage Temperature	-40 - 60 °C
Storage Humidity	10 - 90% non-condensing
Printer Safety	EMC / RMC
Warranty	
Hardware	2 Year Return to Base
Print Head	2 Year Return To Base (25km or 6 months on print head)
Package Contents	
Package Contents	Printer, Quick Start Guide, USB cable, Power Cord, Product Safety Guide, Paper Core
Optional Accessories	
Dual Bluetooth & Wi-Fi	PA-WB-001
Peeler	Not supported
Cutter	Not supported



**Working with you for a better environment**

At Brother, our green initiative is simple. We strive to take responsibility, act respectfully and try to make a positive difference to help build a society where sustainable development can be achieved. We call this approach Brother Earth.



All specifications correct at the time of printing and are subject to change. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies.

**Brother Empowers**



Brother Corporate Solutions



Brother International Australia



BrotherAU

**brother**  
at your side