

Gladius Smart

15" Fan-less Touch POS Terminal
with Various I/O Options



Gladius Smart is a fan-less, aluminum POS terminal with Intel® Atom™ D525 1.8GHz Dual-Cores processor. With a thoughtful modularized integration concept, Gladius Smart can be transformed into various kinds of POS operations by detaching the all-in-one display and combining it with various kits such as a wall-mount version with integrated scanner or a countertop version with integrated printer.



Features

Flexible I/O Connectivity for Various Peripherals

With two I/O panels (1st Standard, 2nd Optional), there are at least 5 options of Interchangeable extended I/O panels that can be selected and replaced by system integrators.

Hidden Power Adapter in Stand for Space Saving

The aluminum stand can not only store the power adaptor under its base, but also provides cable management for connected peripherals.

Many Modularized Integrations

Offerings include various physical and functional integrations such as a wall-mount version integrated with a scanner or a countertop version integrated with a printer.

One-step Quick HDD Replacement Mechanism


HDD can be directly accessed and replaced without removing the cabling, reducing the maintenance time and costs.

Built-in Customer Display for Cost Saving

Customer display is integrated on the console eliminating the need to purchase a pole display.



I/O Interface



Specifications

| Model | AL-7435 |
|-------------------------------|---|
| Processor | Intel® Atom™ D525, 1M L2 Cache, 1.8GHz |
| System Memory | 1GB Standard, Maximum 4GB (1x204-pin DDR3) |
| Power Supply | 150W (12V / 12.5A) External Power Supply Integrated with Base |
| Storage Device | 1 x 2.5" SATA HDD |
| Graphics | Intel® GMA 3150 |
| Speaker | Internal Speaker 2W x 2 |
| Construction | Aluminum Die-casting + SECC |
| Housing Color | Black |
| Touch LCD Display | |
| Size / Resolution | 15" TFT-LCD/ 1024 X 768 |
| Brightness (Backlight Type) | 250 (CCFL) / 450 cd/m ² (LED) |
| Touch Screen | 5-Wire Resistive Touch / Capacitive Touch |
| Panel OSD Control | Power On / Off, Brightness Up / Down |
| I/O Ports | |
| Serial Port | 3 x Internal: COM 6 (LCM), COM A, COM B (Reserved) 3 x External: COM 1, COM 2 (DB9), COM 4 (RJ-45) |
| USB Port | 4 x Internal (1 Touch, 1 Card Reader Module, 2 Reserved), 5 x External (4 Rear + 1 Side) |
| Cash Drawer Port | 1 x RJ11 (12V) |
| Printer Port | 1 x Bi-directional Parallel port |
| Keyboard / Mouse | 1 x PS/2 |
| LAN Port | 1 x RJ45 Giga LAN |
| PCI Slot | 1 x Mini PCI-e (Internal) |
| Audio Port | 1 x Line Out |
| VGA Port | 1 x VGA |
| DC Output | 1 x 12V DC Jack 2.5 mm |
| Optional I/O Board | |
| Type A | Serial Port: COM A & COM B (RJ45) with RI / 5V / 12V Selectable; DC Output: 1 x 24V; 1 x Mic In |
| Type B (Special Requirements) | Serial Port: COM A & COM B (RJ45) RI / 5V / 12V Selectable; Powered USB Port: 1 x 24V; 1 x Mic In |
| Type C | Serial Port: COM A & COM B (RJ45) RI / 5V / 12V Selectable; Powered USB Port: 1 x 12V; 1 x Mic In |
| Type D (Special Requirements) | Powered USB Port: 1 x 12V & 1 x 24V; 1 x Mic In |
| Type E (Special Requirements) | Cash Drawer Port: 2 x 24V ; 1 x Mic In |
| OS Supported | |
| Windows | Windows XP, POSReady 2009, Windows 7, POSReady 7 |
| Linux | Per Request |
| Physical Dimensions | |
| Dimensions (W x H x D) | 382 x 358 x 294 mm |
| Environment | |
| EMI / Safety | CE, FCC Class A |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F) |
| Storage Temperature | -10°C ~ 55°C (14°F ~ 131°F) |
| Relative Humidity | 10% ~ 90% (Non-condensing) |
| Optional Peripherals | |
| Magnetic Stripe Card Reader | Integrated MCR Module (Single / Dual / Triple Track Selectable) |
| MCR 3-in-1 | Integrated MCR / Smartcard / Fingerprint or RFID 13.56 MHz |
| Wireless LAN | Integrated 802.11 b/g/n Wireless Module |
| Base Integrated Devices | RFID 13.56 MHz / Fingerprint Reader / i-Button |