



# I-Series 2.0 for Android

All-in-One Touchscreen Signage



**Integrated Touch**



**Commercial Grade**



**2-Year Warranty**

## Product Overview

Elo's newly upgraded I-Series 2.0 for Android™ combines commercial-grade reliability with the powerful Android Qualcomm® Snapdragon™ processor. Delivering 2X the performance of its predecessor, the I-Series 2.0 brings it all with an integrated TouchPro® PCAP 10-touch display, Android 7.1 (Nougat) and optional Power-over-Ethernet (POE) - all in a compact responsive AiO computer. Available in white and black, the AiO offers a variety of mounting options with the flexibility needed to survive the rigors of continuous public use for in-store interaction, point of sale, self-service, wayfinding, corporate and hospitality environments.

Combine the I-Series with Elo's cloud-based management software, EloView® designed to simplify and automate deployment of Elo interactive displays across the globe. EloView, a software-as-a-service (SaaS) platform, includes OS management (including remote and silent updates), kiosk lock-down, automatic provisioning and device management. The platform also offers virtual GPS capabilities enabling a location to be set (latitude/longitude) remotely for each device, so that content may be localized per device or across all locations.

**Available in 10", 15" or 22" widescreen sizes with high-performance computing and sleek edge-to-edge glass PCAP touchscreen**

**Power-over-Ethernet and Virtual GPS enable flexible installations and customized content delivery via applications**

**Optimize deployments with cloud-based configuration, monitoring and scheduling**

**Modern design with flexible mounting in portrait, landscape and table-top orientation**

## I-Series 2.0 for Android Touchscreen Signage

| Specifications          | 10-inch model   | 15-inch model  | 22-inch model  |
|-------------------------|---|--|--|
| Bezel Color             | Black & White   |  |  |
| Diagonal Size           | 10.1" (256.54mm)  | 15.6" (396.24mm)   | 21.5" (546.10mm)   |
| Operating System        | Android 7.1 with EloView content deployment and management  |  |  |
| Processor               | Qualcomm® Snapdragon™ APQ8053 2.0GHz octa-core Processor  |  |  |
| Memory                  | Standard - 3GB DDR3L; Value - 2GB DDR3L   |  |  |
| Storage                 | Standard - eMMC 5.1 32GB SSD; Value - 16GB SSD  |  |  |
| I/O Ports               | Standard - Micro HDMI output, Micro SD slot, Ethernet 1x LAN (Gigabit), GPIO, 1x USB 3.0, 4x microUSB<br>Value - Ethernet 1x LAN (Gigabit), 1x USB 3.0 support, Micro SD slot, GPIO |  |  |
| Wireless                | 802.11 b/g/n/ac + Bluetooth 4.1   |  |  |
| Webcam                  | Auto exposure; Auto Gain Control; Sharpness/Brightness/Contrast control; Max resolution: 1920 x 1080 30fps (standard model only)  |  |  |
| Speakers                | Two 2W stereo internal speakers   |  |  |
| Audio                   | Microphone and headphone support is available via an optional the USB adaptor (Vantech NBA-120U).   |  |  |
| Active Display Area     | 8.54" x 5.34" (216.96mm x 135.60mm)   | 13.55" x 7.62" (344.16mm x 193.59mm)   | 18.74" x 10.54" (476.06mm x 267.79mm)                          |
| Display Technology      | 1280 x 800 @ 60Hz (native) active matrix TFT LCD with LED backlight   | Full HD 1920 x 1080 @ 60Hz (native) active matrix TFT LCD with LED backlight                 |  |
| Touch Technology        | TouchPro PCAP (Projected Capacitive) - up to 10 touches   |  |  |
| Aspect Ratio            | 16:10   | 16:9   | 16:9   |
| Number of Colors        | 8-bit (16.7M)   | 6-bit (262K)   | 6-bit (Hi-FRC; 16.7M)  |
| Brightness              | LCD Panel 400 nits; PCAP: 344 nits  | Standard - LCD Panel 300 nits; PCAP: 258 nits<br>Value - LCD Panel 220 nits; PCAP: 189 nits  | LCD Panel 250 nits; PCAP: 215 nits                             |
| Response Time           | 25 ms   | Standard - 30 ms; Value - 12 ms  | 14 ms  |
| Viewing Angle           | Horizontal: ±85°; Vertical: ±85°  | Standard - Horizontal: ±85°; Vertical: ±85°<br>Value - Horizontal: ±45°; Vertical: 20° & 40° | Horizontal: ±89°; Vertical: ±89°                               |
| Contract Ratio          | 800:1   | Standard - 800:1; Value - 500:1  | 1000:1   |
| Power                   | AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz  |  |  |
| Power Consumption       | ON: 10.2W / OFF: 0.4W / SLEEP: 5.0W   | ON: 13W / OFF: 0.4W / SLEEP: 4.5W  | ON: 16W / OFF: 0.5W / SLEEP: 4.0W                              |
| Power Cables            | Included - North American, European or UK   |  |  |
| Dimensions* (W x D x H) | 10.06" x 7.13" x 0.99"<br>(255.41mm x 181.11mm x 25.1mm)  | 15.23" x 9.77" x 1.11"<br>(386.74mm x 248.17mm x 28.3mm)                                     | 20.63" x 12.75" x 1.39"<br>(523.9mm x 323.9mm x 35.2mm)        |
| Shipping Dimensions     | 12.99" x 9.84" x 5.51"<br>(330mm x 250mm x 140mm)   | 5.90" x 11.81" x 18.50"<br>(150mm x 300mm x 470mm)   | 7.08" x 15.75" x 23.62"<br>(180mm x 400mm x 600mm)             |
| Weight                  | Unpackaged: 1.94 lbs (0.88 kg)<br>Packaged: 4.56 lbs (2.07 kg)  | Unpackaged: 3.5 lbs (1.59 kg)<br>Packaged: 7.20 lbs (3.27 kg)                                | Unpackaged: 9.47 lbs (4.3 kg)<br>Packaged: 16.10 lbs (7.30 kg) |
| Temperature             | Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)  |  |  |
| Humidity                | Operating: 20%-80%; Storage: 5%-95%   |  |  |
| Mounting Options        | 75 mm x 75 mm   | 75mm x 75mm & 100mm x 100mm  | 100mm x 100mm  |
| Peripheral Mounting     | Standard - 4x microUSB side ports available; Value - Peripheral mounting is not available   |  |  |
| Real-Time Clock         | Lithium-ion battery   |  |  |
| Sealing                 | Touchscreen sealed to LCD   |  |  |
| MTBF                    | 50,000 hours demonstrated   |  |  |
| Warranty                | 2 years standard. On-site exchange (U.S. only) and extended warranty (U.S. and EMEA) available  |  |  |
| Regulatory Approvals    | UL/cUL, FCC, IC, CE, CB, CCC, SRRC, China RoHS, VCCI, MIC, RCM  |  |  |
| What's in the Box       | I-Series 2.0 device, North American Power Cable, European or UK Power Cable, 1x Power Brick, Quick Install Guide, Screws for cable cover door (located in the power/Ethernet bay)   |  |  |

## Ordering Information

| Family            | Part Number            | Description            | Color           | Memory | Storage | Availability    |
|-------------------|------------------------|------------------------|-----------------|--------|---------|-----------------|
| Standard versions | E610902                | ESY10i1-2UWA-0-NA-GY-G | Black           | 3GB    | 32GB    | Worldwide       |
|                   | E611296                | ESY15i1-2UWB-0-AN-GY-G | Black           |        |         | Worldwide       |
|                   | E611675                | ESY22i1-2UWB-0-AN-GY-G | Black           |        |         | Worldwide       |
|                   | E614194                | ESY10i1-2UWB-0-AN-WH-G | White           |        |         | Worldwide (MTO) |
|                   | E614592                | ESY15i1-2UWB-0-AN-WH-G | White           |        |         | Worldwide (MTO) |
| E614981           | ESY22i1-2UWB-0-AN-WH-G | White                  | Worldwide (MTO) |        |         |                 |
| Value versions    | E611101                | ESY10i1-2UWC-0-AN-GY-G | Black           | 2GB    | 16GB    | Worldwide       |
|                   | E611480                | ESY15i1-2UWC-0-AN-GY-G | Black           |        |         | Worldwide       |
|                   | E614391                | ESY10i1-2UWC-0-AN-WH-G | White           |        |         | Worldwide (MTO) |
|                   | E614786                | ESY15i1-2UWC-0-AN-WH-G | White           |        |         | Worldwide (MTO) |

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### North America

Tel +1 408 597 8000  
Fax +1 408 597 8050  
elosales.na@elotouch.com

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
elosales@elotouch.com

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
www.elotouch.com.cn

### Latin America

Tel +52 55 2281 6958  
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and EloView are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2018 Elo Touch Solutions, Inc. All rights reserved. 18012AES00010

