

Element P100-AM

Anti-microbial 2D Hand-held Barcode Scanner

With its comfortable, ergonomic design, disinfectant ready casing and unmatched scanning performance, the new Element P100-AM hand-held scanner offers Anti-microbial casing, containing Nano Silver Antibacterial Technology and a superior out-of-box experience for scan-intensive applications.



- > Anti-microbial scanner, contains Nano Silver Antibacterial Technology
- > The latest mainboard and image scanning technology, which can greatly improve the speed of decoding
- > A solid and durable design
- > Intelligent infrared and aiming auxiliary system for a comfortable and convenient scanning experience
- > Plug and play interface, which can be quickly used with a variety of host devices



Smooth scanning



Comfortable grip

Technical Specifications - Element P100-AM

Item		Parameter	
Scanning	Image Sensor	CMOS	
	Pixel	640 x 480	
	Illumination	Infrared LED	
	Focus	Infrared LED	
	Symbologies	2D:	PDF417, QR Code, Data Matrix, HanXin, Maxicode, Postal Codes, etc.
		1D:	Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand etc.
	Resolution	≥4mil	
	Typical DOF	5mil Code39: 20mm–150mm 13mil EAN: 30mm–300mm 6.7mil PDF417: 25mm–130mm 10mil DM: 15mm–100mm 20mil QR: 15mm–210mm	
	Recognition Sensitivity	Pitch±60°, Tilt360°, Skew±60°	
	FOV	Horizontal: 32°, Vertical: 25°	
Symbol Contrast	≥20%		
Physical	Dimension (mm)	83D x 67W x 175H	
	Weight	128g	
	Scanner Interface	RJ-45 Crystal Head	
	Housing Materials	PC+TPU	
	Notification	Buzzer, LED Indicator	
	Interface	RS-232 Serial Port, USB, USB Virtual Serial Port	
	Trigger Method	Manual keystroke, Automatic induction, Continuous Recognition	
Electrical	Operating Voltage	5VDC±10%	
	Operating Current	Standby: 100mA Working: 230mA	
	Power	Standby: 0.5W Work: 1.15W	
	Operating Temperature	-20°C~+50°C	
	Storage Temperature	-40°C~+70°C	
	Relative Humidity	5%~95% (No Condensation)	
	ESD	±15 kV (Air discharge) ±8 kV (Direct discharge)	
	Environment Luminosity	0~100, 000LUX	
	Anti-shock Ability	1.5m	
	Protection Grade	IP42	
	Certification	CE FCC ROHS	
	Cable	USB, RS232	
	AC Adapter	5V, coordinate with RS-232 cable to power the scanner	
Test Condition	Environment temperature=23°C Environment illumination=300LUX DOF scanning depends on the resolution, contrast and illumination of barcode.		