Packing List



Notes: Items in the package are dependent on the actual order.

Appearance and Components





Front

Paper Installation

1. Pull the cover open deflector rod to open the printer cover.



2.In the correct direction of the roll paper, install the roll paper.



3.Pull out some roll paper, and close the printer cover.4.Tear the extra paper of the printer.



Power Supply

1.Connect power adapter to printer.

- 2.Connect power adapter to power cord.
- 3.Plug the other side of power cord into the socket outlet.





Quick Start Guide

POS80D

Bluetooth Settings

Following screen-shots are under Windows 7.

BT - Utility Tool

Turn on the printer -> turn on the main device -> run the BT program (Use a BT Dongle if the main device has no BT function)
-> right click the BT icon (at the lower right part of the screen)
-> choose "Add a Bluetooth Device", -> choose "BT Printer"-> click "next" -> the BT printer is successfully added to the main device.



Select a device to add to this computer

Windows will continue to look for new devices and display them here.

S.	Bluetooth Phone	S and	S.E.	Bluetooth Phone		•
	BT Printer Bluetooth Printer			OKN31-A444 Bluetooth Other		
	HM-A300 Bluetooth Printer				•	
	MT53_DA667C Bluetooth Printer					Ŧ

What if Windows doesn't find my device?



Note: If you are required to enter the password to add the BT printer, please obtain the password from the self-test page of the printer.

2. Under "Devices and Printers", right click the BT Printer icon and choose "Properties" -> choose "Services"-> find COM3, which is connected to the BT port.



3. Install the Utility tool-> open the Utility tool->Modify Printer".

Printer List:	
POS80D USB POS80D	Add Printer
	Modify Printer
	Delete Printer
	Connection Test

4. Choose "POS80D" for printer driver, choose "COM3" for system port, click "OK", so the printer is connected through BT.

inter driver:	POS80D	
ortInfo		
Port type: (OM	~
System Port:	COM3	~
Baud rate:	115200	~
Parity:	None	~
Stop Bits:	1	~
Notes:		

Printer List:

POS80D/COM | COM3, BaudRate_115200, None, One |

5.Click "Advanced Settings"-> click "Bluetooth Setting"-> type in new Bluetooth name and password -> click "Set" -> restart the printer to take effect.

	Advanced Settings			Bluetooth Setting		
[Se	t Bluetooth		×		
		Bluetooth Parameter	-	 		
		Bluetooth Name:	BT Printer	(<=10 ASCII Chars)		
		Password:	0000	(4 Numeral)		
		✓ Simple Pairing				
			Set	Close		

Bluetooth - Windows Driver

6. Take the same steps of 1.~2. -> install Windows Driver program -> right click POS80D icon under "Devices and Printers -> choose "Printer properties" -> choose "Ports" -> choose COM3 -> click "OK".

		Printer p	roperties				
POS80D Properties							
General Sharin	General Sharing Ports Advanced Color Management Security About						
Print to the following port(s). Documents will print to the first free checked port.							
Port	Description		Printer		^		
LPT1: Printer Port							
LPT2:	LPT2: Printer Port LPT3: Printer Port COM1: Serial Port COM2: Serial Port				=		
LPT3:							
COM1:							
COM2:							
COM3: Serial Port							
COM4:	COM4: Serial Port				-		
Add P	Add Port		Delete Port		gure Port		
Enable bid	Enable bidirectional support						
	ner pooning						
			ОК	Cancel	Apply		

7. Choose "General" under "Printer properties" and click "Print Test Page" to print the test page. If the printing is failed, check whether Bluetooth is disconnected or the corresponding COM port is occupied.