



Epson TM-H6000V

Multifunction/Hybrid POS Printer

This integrated multifunction printer is capable of receipt printing, slip printing and cheque processing in one unit. The retail-hardened TM-H6000V offers both reliable and useful connectivity to business users while maintaining a very low total cost of ownership. It is ideal for businesses requiring cheque-processing facilities as point of sale and print receipts with the same unit.

- More productivity
- Reliable and efficient
- Full range of connectivity features
- Advanced print options that reduce paper usage
- Two-year warranty

Epson TM-H6000V



More productivity

Ideal for busy environments, the TM-H6000V offers a selection of features that help businesses boost overall efficiency. It prints at speeds up to 350mm/s, offers fast checque processing and a swift auto-cutter.

Reliable and efficient

Product Specifications

In fast paced environments, it is essential to minimise downtime. The TM-H6000V is a dependable solution with the thermal printer now effective for printing up to 200km of receipts, while its auto-cutter is capable of three million cuts.

Range of connectivity features

The TM-H6000V is designed to handle all types of POS solutions with ease. It is flexible enough to adapt to the demands of modern retail environments including Server Direct Print (SDP) to print and display data from external servers, as well as multiple interfaces for tablet and PC coexistence.

Stay tuned with the trends in the POS Market

Looking for a future-proof printer that's simple and quick to set-up? ePOS-Print, ePOS-display and NFC tagging make it possible to incorporate new functionalities at the Point of Sale and allow quick tablet POS set-up.

Print Specification	Receipt	Slip	Endorsement Printer
PRINT METHOD	Thermal line printing	9-pin serial impact dot matrix	9-pin serial impact dot matrix
PRINT SPEED	Up to 350mm/sec	Up to 5.7 lps (40 columns, 17.8 cpi)	Up to 4.0 lps (21.2cpi)
PRINT FONT	9 x 17 / 12 x 24 / 10x20	5 x 9 / 7 x 9	5 x 7
COLUMN CAPACITY	56 / 42 / 50 columns	60 / 45 columns	40 columns
CHARACTER SIZE	0.99 x 2.4mm (W x H)	1.56 x 3.1mm (W x H)	1.09 x 2.41mm (W x H)
	1.41 x 3.39mm (W x H)	1.24 x 3.1mm (W x H)	
	1.27 x 2.82 (W x H)		
BARCODE	One- and two-dimensional and composite	n/a	n/a
PAPER DIMENSIONS	$79.5 \pm 0.5 x$ diameter 83.0mm	68-230mm (W), 68-297mm (L)	n/a
PAPER THICKNESS	0.048 to 0.08 mm	0.09 to 0.47mm	0.09 to 0.31 mm
COPY CAPABILITY	n/a	One original & three copies	One original & 2 copies
INKED RIBBON	n/a	ERC-32B (Black)	ERC-43B (Black)
RIBBON LIFE	n/a	4,000,000 characters	3,000,000 characters
POWER CONSUMPTION	Approx. 1.8 A Standby approx. 0.1a minimum	Approx. 1.7 A	Approx. 1.7 A
RELIABILITY	MTBF 360,000 hours	180,000 hours	180,000 hours
	MCBF 96,000,000 lines	29,000,000 lines	29,000,000 lines
CHARACTER SET	95 Alphanumeric, 18 international sets, 128 x 12 extended graphics set		
INTERFACE	Built-in USB, and Ethernet. Wi-Fi option. UIB option for Serial, parallel and Powered USB		
DATA BUFFER	45 bytes or 4 KB (up to 384 KB for graphic memory)		
AUTOCUTTER	High-speed with partial cut		
SUPPLY VOLTAGE	24 VDC ± 7 %		
D.K.D. FUNCTION	2 drivers		
SENSORS	Cover open, Top of form, Bottom of form, Slip eject, Roll paper near end, Roll paper end		
FACTORY OPTIONS	MICR device, Endorsement printer, 58mm width paper guide PG-58II, Power supply unit (PS-180)		
COLOUR	White (ENNB.5), Black (EBCK)		

VCCI class A, FCC class A, CE marking, AS/NZS CISPR 32:2013 Class A (EN 55032 (2012) Class A)

cpi: characters per 25.4mm (characters per inch) lps: lines per second

RoHS compliant

Approximately 4.4Kg



www.epson.com.au

ENVIRONMENTAL STANDARDS

EMI STANDARDS

Weight

SAFETY STANDARDS

Overall Dimensions

EPSON NEW ZEALAND Level 2, 7-9 Fanshawe Street Auckland, 1010 0800 237 766 www.epson.co.nz

UL / CSA / TÜV (EN60950) / GOST-R (IEC60950. CISPR22)

186mm (W) x 278mm (D) x 181mm (H)

ABN 91 002 625 783 05/19



EXCEED YOUR VISION