



Model	BP-325	BP-363
Processor	Intel® Atom™ D525, 1MB L2 Cache, 1.8GHz	Intel® Celeron J1900 up to 2.42 Ghz
System Memory	1GB Standard, Maximum 4GB (1 x 204-pin DDR3)	2GB Standard, Maximum 8GB (1 x 204-pin DDR3L)
Power Supply	60W (12V / 5A) External Power Adaptor	150W (12V / 12.5A) External Power Adaptor
Storage Device	1 x 2.5" SATA HDD or SATA SSD	1 x 2.5" SATA HDD or SSD
Optional Storage Device	1 x SATA DOM	N/A
Graphic	Intergrated	Intel HD
Construction	Aluminum Die-casting + Plastic	
Housing Color	Iron Grey	
I/O Ports		
Serial Port	2 x External: COM2 (DB9) COM4 (RJ45)	3 x External: COM1(RJ45) with RI / 5V / 12V Selectable
USB Port	5 x External (1 Front, 4 Rear)	6 x External (USB 2.0 x 3; USB 3.0 x 1; USB 2.0 x 1 Front; Powered USB 24V x 1)
Printer Port	1 x Bi-directional Parallel Port	By Request
Cash Drawer Port	1 x RJ11 (12V)	1 x RJ11 (12V / 24V)
Keyboard / Mouse	1 x PS/2	N/A
LAN Port	1 x RJ45 Giga LAN	1 x RJ45 Giga LAN
Expansion Slot	1 x Mini PCI-e (Internal)	1 x Mini PCI-E (Internal / USB + PCI-E x 1)
Audio Port	1 x Line Out	N/A
Video Port	1 x VGA, 1 x DVI-D	1 x VGA ; 1 x HDMI
DC Output	1 x 12V DC Jack 2.5 mm	N/A
Optional I/O Board		
Type A	Serial Port: COM1, COM3, COM5, COM6 (DB9); 1 x Mic-in	Serial Port: COM A & COM B (RJ45) with RI / 5V / 12V Selectable; DC Output: 1 x 24V; 1 x Mic-in
Type B	Serial Port: COM1, COM6 (DB9), COM3, COM5 (RJ45) Video Port: 1 x VGA; DC Output: 1 x 24V; 1 x Mic-in	Serial Port: COM A & COM B (RJ45) RI / 5V / 12V Selectable; Powered USB Port: 1 x 24V; 1 x Mic-in
Type C	Serial Port: COM1, COM6 (DB9) COM3, COM5 (RJ-45) DC Output: 1 x 24V DIN 3p for Printer; 1 x Mic-in	Serial Port: COM A & COM B (RJ45) RI / 5V / 12V Selectable; Powered USB Port: 1 x 12V; 1 x Mic-in
Type D	SerialPort: COM1, COM3, COM5, COM6 (DB9) LAN Port: 1x RJ45 Giga LAN; 1 x Mic-in	N/A
Type E	N/A	Cash Drawer Port: 2 x 24V (RJ11) ; 1 x Mic-In
Type G	N/A	Powered USB Port: 3 x 12V
Type H	N/A	Powered USB Port: 1 x 24V, 2 x 12V
OS Supported		
Windows	Windows XP, POSReady 2009, Windows 7, Windows Embedded POSReady 7	Windows 7, Windows Embedded POSReady 7, Windows 8.1, Windows Embedded 8.1 Industry
Physical Dimensions		
Dimensions (W x H x D)	230.24 x 65 x 190.04 mm	
Carton Dimensions (W x H x D)	400 x 130 x 245 mm	
Weight	2.4kg (Net), 3.5kg (Gross)	

Fanless Compact POS BOX

BP-325 / BP-363



FEC

BP-325 BP-363

Compact, low noise, low consumption, FEC design.

Featuring Intel Bay Trail / Atom D525, the BP-363 / 325 is the perfect POS box that works with your creativity on terminal placement. With numerous I/O options, never again worry about peripheral connectivity.

Features

BP-325



Type A: Standard



Type B: Dual VGA



Type C: Printer 24V



Type D: Dual LAN

BP-363



Base Configuration

Optional I/O



Type A



Type B



Type C



Type E



Type G



Type H



Optional SATA DOM (BP-325 only)



One step access to the SATA HDD or SSD for easy serviceability.



Power button, internet connection indicator, hard disk indicator and USB port is located in the front face for quick maintenance.



The thermal fin design, increasing heat transfer effectiveness, keeping it cool



Can be easily mounted onto any flat surface with a FEC universal mount.



The motherboard is easily accessible for efficient upgrades.



- Combine with AerMonitor and other add-on devices for a complete point of sale solution.
- Multiple I/O interface choices for different applications
- Can be used as a kiosk engine to power self-service solutions
- Modular design for easy serviceability



Weighs only 2.4 kilograms



It is extremely compact measuring at 23 centimeters in width, 6.5 centimeters in height and 19 centimeters in depth.



Use your own customized Logo