

XM-3010W



The FEC new generation product – Xmonitor 3000 Series, which redesigned for XPPC, provides docking type and Arm type for easy connect.





Specifications



Display

- 10.1" TFT , 1280 x 800



Brightness

- 400 nits



Speaker

- 2 x 2W Internal Speaker



Touch

- Non-Touch
- True-Flat PCAP



MTBF

- 30K Hours



Power

- DP Version:
12V DC-in
- Smart DD Version:
20V DC (Power from Smart DD)
- AD Board Version:
12V DC (Power from VGA, USB
DP)



Mounting

- Docking Type
- Arm Type
- VESA 75 x 75 mm



Certification

- FCC / CE Class B



Appearance

- Plastic + ABS
- Galaxy Grey



Temperature

- Operation: 0 °C ~ 40 °C (32 °F ~ 104 °F)
- Storage: -20 °C ~ 60 °C (-4 °F ~ 140 °F)



Dimensions (W x H x D)

- Product: 260 x 178 x 30 mm
- Carton: 313 x 208 x 108 mm



Weight

- Display Net 0.8 kg
- Display Gross 1.3 kg



Port

- Smart DD Version:
 - 1 x Smart DD in
 - 1 x Smart DD out
- AD Board Version:
 - 1 x Video Port
 - 1 x VGA (12V Power)
 - 1 x USB DP
 - 1 x USB 2.0 Type B
 - 1 x DC-in 12V
 - 1 x Line-in



Optional

- Smart DD/AD Board Version:
 - Compatible with XPOS Add-on device. (Supports Device on Right Side)