

Overview

HP Engage One Pro G2 All-In-One system

FRONT VIEW




Overview

REAR VIEW



Overview


HP Engage One Pro G2 Column hub



IMPORTANT: To avoid damage to the computer, DO NOT plug a telephone cable into the cash drawer jack.

Overview

HP Engage One Pro G2 VESA hub



IMPORTANT: To avoid damage to the computer, DO NOT plug a telephone cable into the cash drawer jack.

Overview


HP Engage One Pro G2 Advanced Fan-less Hub



IMPORTANT: To avoid damage to the computer, DO NOT plug a telephone cable into the cash drawer jack.

Overview

ENGAGE ONE PRO USB-A (HUB-LESS) DONGLE



IMPORTANT: To avoid damage to the computer, DO NOT plug a telephone cable into the cash drawer jack.

Overview

Component Breakdown

- | | |
|--|---|
| 1. Head unit screen sizes: 3 Choices
15.6", 19.5", 23.8"
Landscape or portrait orientation | 3. Stability Base Plate or Counter mount & U-Shape Adapter |
| 2. Stand: 3 choices:
Advanced stand,
Pro stand,
Slim VESA wall mount | 4. Hub: 4 Options based on I/O requirements:
Column hub
Advance hub,
VESA mount hub,
Hub-less |

Not shown: Head unit connects with hub through a 140W Cable with secure screwed to connectivity base

Overview

Component Breakdown

HP Engage One Pro G2 Stand Features

1. Advanced Stand-Dual hinge with 12° vertical associate side flip to 140° on customer side
2. Engage One Pro stand- tilt 40° – 120°




Overview

Component Breakdown

HP Engage One Pro G2 Stand Features

3. HP Engage One Pro G2 AiO Slim VESA mount (100x100mm)



4. HP Engage One Pro G2 AiO Advanced* Stand Clean Counter Mount No stability plate- includes Counter Mounting Bracket** (Requires 94mm hole)



5. HP Engage One Pro G2 AiO System Advanced* stand with Stability Base Plate



Overview

At A Glance

- Choice of 2 colors: Ebony Black & Ceramic White*
*White only available in 15.6" and 23.8"
- Choice of 2 orientations: Landscape & portrait
- With or without Camera
- Choice of 3 Long lifecycle performance All-in-One (AiO) Retail System for retail and hospitality markets operator display:
 - 15.6" diagonal, FHD(1920 x 1080), touch, IPS, UWVA, anti-glare, 400 nits, 45% NTSC
 - 19.5" diagonal, FHD(1920 x 1080), touch, VA, UWVA, anti-glare, 450 nits, 72% NTSC
 - 23.8" diagonal, FHD(1920 x 1080), touch, IPS, UWVA, anti-glare, 625 nits, 72% NTSC**NOTE: Actual brightness will be lower with touch screen**
- Choice of 2 column stand:
 - HP Engage One Pro G2 Advanced stand
 - HP Engage One Pro stand
- Choice of Mounting:
 - Clean counter- Place the connectivity hub under the counter
 - All together- Place the hub directly under the stand
 - Slim VESA wall mount- Place the head unit on the wall
 - Pole mount- Place the head unit on a single or back-to-back pole
- Intel®Q670E chipset, 35W Processors
- Processor choices:
 - Intel® Celeron® G Series
 - Intel® Celeron® G6900TE
 - Intel® Core™ 14th Generation
 - Intel® Core™ i3 14th generation processor
 - Intel® Core™ i5 14th generation processor
 - Intel® Core™ i7 14th generation processor" Intel® Pentium® processor
 - Integrated: Intel® UHD Graphics 710 on Celeron & Pentium; Intel® UHD Graphics 730 on i3 and i5, Intel® UHD Graphics 770 on i7
 - Intel® Ethernet Connection Intel® I219-LM GbE, vPro® integrated network connection from head unit
 - RTL8153CH Ethernet Connection from Advanced hub
 - Intel® Wi-Fi 7 BE200 and Bluetooth® 5.4 wireless card, vPro®;
 - Intel® Wi-Fi 7 BE200 and Bluetooth® 5.4 wireless card, non-vPro®
 - Intel Wi-Fi 6E AX211 Wi-Fi 6E and Bluetooth® 5.3 wireless card, non-vPro®
- Operating System choices:
 - Windows 11 Pro 64-bit / Windows 10 IoT Enterprise 2021 LTSC64 / Windows 11 IoT Enterprise 2024 LTSC64
 - FreeDOS 3.0
 - SUSE Linux® Enterprise Server 15
 - Google ChromeOS Flex
- Connectivity Base Choices
 - HP Engage One Column hub:
 - HP Engage One VESA hub
 - HP Engage One Advanced Fan-less hub
 - Hub-less
- Integrated peripheral options (can also be purchased and installed separately)
- HP Engage One Pro MSR
- HP Engage One Pro G2 Bar Code Scanner (choose between 3 locations: left, right, bottom) of the head unit
- HP Engage One Pro Fingerprint Reader
- HP Engage One Pro 6x6 Customer facing display with 2x20 line display emulation **
**The 2x20 line display emulation can be used on 6.6" CFD and future CFDs for Engage One Pro Virtual Line Display will work with any display. It defaults to 2x20, it can also be used for any other size line display such as 3x16 or 3x20, 5x10
- Virtual Line Display will work with any display. It defaults to 2x20,, it can also be used for any other size line display such as 3x16 or 3x20, 5x10
- Industry-standard 100mm VESA mounting pattern allows for flexible use without the optional stand (Mounting hardware sold separately)

Overview

- (2) Two DDR5 Memory Slots (64 GB Maximum)
- Trusted Platform Module (TPM2.0)
- HP BIOSphere with HP Sure Start technology
- Cable Management Features-RJ45 extension
- ENERGYSTAR®certified configurations available, EU Compliant, RoHS2 Compliant, EPEAT®registered configurations available
- Standard Warranty Options – 90/ 90/ 90, 1/ 1/ 1, 3/ 3/ 3; Plus Optional Care Packs
- 2 SODIMM Memory slots with up to 64 GBDDR5 SDRAM Transfer rates up to 5600 MT/s.
- 1x M.2 WLAN expansion slot
- 2xM.2 Storage slots
- 256 GBto up to 4 TB PCIe® NVMe SSDfirstdrive
- 256 GBto up to 4 TB PCIe® NVMe SSDseconddrive
- Integrated HD audio with Realtek ALC3247 codec with standards internal speakers and stereo headphone jack, 2W)
- HP Credential Guard; HP Device Guard; HP Support Assistant; HP BIOSphere with Sure Start Generation 6.0
- HP Sure Sense; HP Sure Click (Standard); HP Sure Admin; HP MIK(SCCM Integration); HP Image Assistant; HP BIOSphere with Sure Start Gen6; HP Client Security Manager Gen7; HP Sure Recover Gen3; HP Sure Run Gen3
- Intel® vPro® with AMT11.0;TPM2.0;HP System Software Manager; HP Image Assistant; HP Client Security Manager
- Display head Ports and Connectors: 1 audio-out; 2 USBType-A5Gbps signaling rate; 2 USB Type- A 5Gbps signaling rate (HP Sleep and Charge); 1 RJ-45 USBNIC;1 140Wdata port Side: 1 Security lock slot
- Choice of 3 connectivity hubs:
 - HP Engage One Pro G2 Column hub:
 - 3x USB Type-A 5Gbps signaling rate
 - 1x RJ-45 NIC
 - 1x DCconnector
 - 3x USB 2.0 Type-A
 - 1x USB Type-C® 5Gbps signaling rate (27 WPower Delivery, Alt Mode DisplayPort™)
 - 1x 140Wdata port
 - 1x P-USB 12V
 - 1x P-USB 24V
 - HP Engage One Pro G2 VESA hub:
 - 3x USB Type-A 5Gbps signaling rate
 - 1x RJ-45 NIC
 - 1x DCconnector
 - 3x USB 2.0 Type-A
 - 1x USB Type-C® 5Gbps signaling rate (27 WPower Delivery, Alt Mode DisplayPort™)
 - 1x 140Wdata port
 - 1x P-USB 12V
 - 1x P-USB 24V
 - HP Engage One Pro G2 Advance fan-less hub
 - 1x cash drawer connector
 - 2x power serials
 - 4x USB Type-A 5Gbps signaling rate
 - 1x RJ-45 NIC
 - 1x DCconnector
 - 1x USB Type-C®5Gbps signaling rate (27 WPower Delivery, Alt Mode DisplayPort™)
 - 1 x140Wdata port]
 - 2x P-USB 12V
 - 1x P-USB 24V
 - Combination of Advance hub with Column hub; Combination of Advance hub with VESA hub.
 - HP Engage One Pro G2 Hub-less
 - 1x USB type-A port and 1xRJ45 pass thru port

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Overview

SECURITY DISCLAIMERS:

HP Essential Security requires Windows 10, includes various HP Sure security features and is available on HP Elite and Workstation products. See product details for included security features.

HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

HP Sure Recover Gen3 is available on select HP PCs and requires an open network connection. Not available on platforms with multiple internal storage drives. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. HP Sure Recover Gen3 requires an open network connection. You must back up important files, data, photos, videos, etc. before use to avoid loss of data.

HP Sure Start Gen6 is available on select HP PCs.

HP Sure Click is only supported on Intel Core i3, i5, and i7 processors.

HP Sure Click, Sure Run, Sure Recover & Sure Sense is supported on Win 10 Pro & Win 10 IoT Enterprise 2019 LTSC; but not on Win 10 IoT Enterprise 2016 LTSC.

For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

HP BIOSphere Gen6 is available on select HP Pro and Elite PCs. See product specifications for details. Features may vary depending on the platform and configurations.

Features

OPERATING SYSTEM

Preinstalled	Windows 11 Pro 64-bit ¹ Windows 10 IoT Enterprise 2021 LTSC Windows 11 IoT Enterprise 2024 LTSC Google ChromeOS Flex FreeDOS 3.0
Certified	SUSE Linux®Enterprise Server 15 ² ; Redhat

NOTE:

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>
2. SUSE Enterprise Linux 15 SP2 YES Certification on a single platform configuration. More information about SUSE

YES certification on <https://www.suse.com/partners/ihv/yes/>

The following features are not supported by SUSE Linux Enterprise Desktop:

- Power Management features
- Multi-touch capabilities
- Systems configured with Linux do not qualify for ENERGY STAR®

3. Only available on certain configurations (please ask sales representative)

Adapters and Cables

- HP USB-C® to DisplayPort
- HP USB-C® to HDMI
- HP USB-C® to VGA
- USB to Serial Port Adapter

NETWORKING/COMMUNICATIONS

- Intel® Wi-Fi 7 BE200 and Bluetooth® 5.4 wireless card, vPro®;*, **
- Intel® Wi-Fi 7 BE200 and Bluetooth® 5.4 wireless card, non-vPro®;*, **
- Intel Wi-Fi 6E AX211 Wi-Fi 6E and Bluetooth® 5.3 wireless card, non-vPro®;*, **
- Realtek RTL8153CH 10/ 100/1000GbE Lan Chip:
 - Supports Ethernet speeds: 10Mbps, 100Mbps, and 1Gbps
 - USB Interface: USB 3.0 for faster data transfer rates compared to USB 2.0
 - Auto-negotiation: Automatically negotiates the best speed (10Mbps, 100Mbps, or 1Gbps) with a connected device
 - Compact size: USB form factor makes it suitable for laptops and desktops with limited space
 - Power Management: Supports features like ACPI and Wake-on-LAN for efficient power consumption

*Wireless access point and Internet service required and not included. Availability of public wireless access points limited. The specifications for the 802.11ax WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the PC to communicate with 802.11ax WLAN devices. Wi-Fi 7 requires a wireless router, sold separately, that supports 802.11be (Wi-Fi 7). Only available in countries where 802.11be is supported.

Features

** Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router.

Requires a wireless router, sold separately, that supports 80MHz and higher channels.

***Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 7 (802.11be) is backwards compatible with prior 802.11ax (Wifi6)specs.

NEAR FIELD COMMUNICATION

NXP NPC300 Near Field Communication Module

PORTS

HP Engage One Pro G2 Head unit I/O:

- 1x 140W data port (PDO cable to Head Unit)¹
- 1x RJ45 vPro NIC
- 1 x 3.5mm Audio Jack support CTIA type
- 4x Integrated USB-A Gen1 Peripherals ports
- 2x USB3.2 G1 Type-A / 900mA
- 2x USB3.2 G1 Type-A / 2.2A

Internal access door for the SSD and USB-Port Type A on Motherboard

Dimensions for USB-Port Type A:

55mm L includes plug / 16mm W / 8mm

HP Engage One Pro G2 Column hub I/O

- 3x USB3.2 G2 Type-A / 900mA
- 1x RJ45 (cable direct from Head unit)
- 1x DC connector
- 1x P-USB 12V
- 1x P-USB 24V
- 1x USB3.2 G1 Type-C® DP Alt Mode / 27W
- 1x 140W data port (PDO cable to Head Unit)¹

HP Engage One Pro G2 VESA hub I/O

- 3x USB3.1 G1 Type-A / 900mA
- 1x RJ45 (cable direct from Head unit)
- 1x DC connector
- 1x P-USB 12V
- 1x P-USB 24V
- 1x USB3.2 G1 Type-C® DP Alt Mode / 27W
- 1x 140W data port (PDO cable to Head Unit) ¹

HP Engage One Pro G2 Advanced Fan-less hub I/O

- 1x RJ12 Cash Drawer
- 2x 12V P-USB
- 1x 24V P-USB
- 2x DB9 P-Serial
- 4x USB3.2 G1 Type A/900mA
- 1x RJ45 USB NIC
- 1x DC connector
- 1x USB 3.1 G2 Type-C® DP Alt Mode / 27W
- 1x 140W data port (PDO cable to Head Unit) ¹

HP Engage One Pro G2 Hubless I/ O

- 1x USB Type A
- 1x DC connector

Features

- 1x RJ45 NIC

NOTE 1: HP 140W port only compatible with the 140W cable included with the product. Cable required for the HP Engage One Pro G2 to operate

USB SPECIFICATION

Speed

Hi-Speed USB 480Mbps signaling rate

USB 5Gbps signaling rate

Terminology

USB 2.0

USB 3.2 Gen 1

SOFTWARE COMPONENTS AND APPLICATIONS

BIOS

- **HP BIOSphere Gen6**
 - Protect and manage the foundation of your POS System
 - Building on over a decade of BIOS security leadership, HP BIOSphere Gen6 offers an ecosystem of protections to help defend your system, including automated protections, customizable safeguards, and easy manageability
- **HP Secure Erase¹**
- **Device Guard Enablement**

Additional features of the HP BIOS Features

- Power-On password

Software

- HP Privacy Settings
- HP Setup Integrated OOB
- HP Easy Clean²
- HP Notifications
- myHP

Manageability Features

- HP Driver Packs
- HP Manageability Integration Kit³
- HP Image Assistant
- HP Smart Support⁴

Notes:

1. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
2. HP Easy Clean requires Windows and will disable the keyboard, display and touchpad only. Ports are not disabled.
3. HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.
4. HP Smart Support is available to commercial customers through your HP Service Representative and HP Factory Configuration Services; or it can be downloaded at: <http://www.hp.com/smart-support>. HP Smart Support automatically collects the telemetry necessary upon initial boot of the product to deliver device-level configuration data and health insights.

Security Management

- HP BIOSphere Gen 6¹
- HP Client Security Manager Gen7⁶

Features

- HP Multi-Factor Authenticate -
- HP SpareKey -
- HP Sure Start⁶
- HP Sure Run⁴ -
- HP Sure Recover⁴-Recover quickly and minimize downtime
 - Driven by the HP Endpoint Security Controller, HP Sure Recover enables users to reimagine their systems quickly and securely using only a network connection – no IT intervention needed.

Other Security Features

- HP Engage One AiO System Biometric Fingerprint Reader (optional)
- Bolt to counter mechanism
- VESA mounting
- Keyed Cable Lock
- Trusted Platform Module TPM 2.0
- Drive lock
- USB enable/disable (via BIOS)
- Power-on password (via BIOS)
- Setup password (via BIOS)
- Tamper Resistant Screw affixed on stand of the system unit, used to secure display head to stand without Quick Released
- HP vPRO Support

Notes:

1. HP BIOSphere Gen6 features may vary depending on the platform and configuration.
2. HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation
3. agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data
4. HP Sure Click, Sure Run, Sure Recover & Sure Sense is supported on Win 10 Pro & Win 10 IoT Enterprise 2019 LTSC; but not on Win 10 IoT Enterprise 2016 LTSC.
5. HP Client Security Manager Gen7 requires Windows
6. HP Sure Start Gen6 is available on select HP PCs.

PROCESSORS

- Intel® Celeron® G6900TE with Intel®UHD710 Graphics (2.4 GHz P-core base frequency, 4 MB L3 cache, 2 P-cores, 2 threads)
- Intel® Core™ i3-14100T with Intel UHDGraphics 730 (2.7 GHz P-core base frequency, up to 4.4 GHz P-core Max Turbo frequency, 12 MB L3 cache, 4 P-cores and 0 E-cores, 8 threads)
- Intel® Core™ i5-14500T with Intel UHD770 Graphics (1.2 GHz E-core base frequency, 1.7 GHz P-core base frequency, up to 3.4 GHz E-core Max Turbo frequency, up to 4.8 GHz P-core Max Turbo frequency, 24 MB L3 cache, 6 P-cores and 8 E-cores, 20 threads), supports Intel® vPro® Technology
- Intel® Core™ i7-14700T with Intel UHDGraphics 770 (0.9 GHz E-core base frequency, 1.3 GHz P-core base frequency, up to 3.7 GHz E-core Max Turbo frequency, up to 5.0 GHz P-core Max Turbo frequency, 33 MB L3 cache, 8 P-cores and 12 E-cores, 28 threads), supports Intel® vPro® Technology

PROCESSORS FAMILY

14th Gen 35W Intel Core™ processors

Features

NOTES:

1. Multi-core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
2. Intel® Turbo Boost technology requires a PC with a processor with Intel Turbo Boost capability. Intel Turbo Boost performance varies

depending on hardware, software and overall system. See <http://www.intel.com/technology/turboboost> for more information.

3. For full Intel® vPro® functionality, Windows 10 Pro 64 bit, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or WLAN card and TPM 2.0 are required. Some functionality requires additional 3rd party software in order to run. See <http://intel.com/vpro>
-

Technical Specifications

INTEL® 14th GENERATION CORE™ vPRO® PROCESSORS

Intel®Core™ i5-14500T with Intel UHD770 Graphics (1.2 GHz E-core base frequency, 1.7 GHz P-core base frequency, up to 3.4 GHz E-core Max Turbo frequency, up to 4.8 GHz P-core Max Turbo frequency, 24 MB L3 cache, 6 P-cores and 8 E-cores, 20 threads), supports Intel® vPro® Technology

Intel®Core™ i7-14700T with Intel UHDGraphics 770 (0.9 GHz E-core base frequency, 1.3 GHz P-core base frequency, up to 3.7 GHz E-core Max Turbo frequency, up to 5.0 GHz P-core Max Turbo frequency, 33 MB L3 cache, 8 P-cores and 12 E-cores, 28 threads), supports Intel® vPro® Technology

The HP Engage One Pro G2 AiO System Retail System features this technology and includes processors that are part of the Intel® Stable Image. Platform Program (SIPP) designed to ensure the stability promise inherent in the value proposition of the HP Engage One Pro G2 AiO System Retail System.

Intel® Advanced Management Technology (AMT) v11.6

An advanced set of remote management features and functionality which provides network administrators the latest and most effective tools to remotely discover, heal, and protect networked client systems regardless of the system's health or power state.

- AMT 11.6 includes the following advanced management function
- Power Management (on, off, reset)
- Hardware Inventory (includes BIOS and firmware revisions)
- Hardware Alerting
- Agent Presence
- System Defense Filters
- SOL/USBR
- Cisco NAC/SDN Support
- ME Wake-on-LAN • DASH 1.1 compliance
- IPv6 Support
- Fast Call for Help - a client inside or outside the firewall may initiate a call for help via BIOS screen, periodic connections, or alert triggered connection
- Remote Scheduled Maintenance - pre-schedule when the PC connects to the IT or service provider console for maintenance. Remote PCs can get required patches, be inventoried, etc. by connecting to their IT console or Service Provider when it's convenient
- Remote Alerts - automatically alert IT or service provider if issues arise
- Access Monitor - Provides oversight into Intel® AMT actions to support security requirements
- PC Alarm Clock
- Microsoft NAP Support
- Host-based set-up and configuration
- Management Engine (ME) firmware roll back
- Wireless AMT functionality on Desktop (WoDT)
- Enhanced KVM resolution

*Some functionality of this technology, such as Intel Active management technology and Intel Virtualization technology, requires additional 3rd party software in order to run. Availability of future "virtual appliances" applications for Intel vPro® technology is dependent on 3rd party software providers. Compatibility with future "virtual appliances" is yet to be determined.

** Intel® Active Management Technology requires an Intel® AMT-enabled chipset, network hardware and software, as well as connection with a power source and a corporate network connection. Setup requires configuration by the purchaser and may require scripting with the management console or further integration into existing security frameworks to enable certain functionality. It may also require modifications of implementation of new business processes.

Technical Specifications

OPERATOR DISPLAY*

15.6" Diagonal Wide Aspect, Projective Capacitive, Anti-glare, Anti-smudge, IPS Display with Projective Capacitive Touch

Touch Technology	Projected Capacitive Touchscreen
Resolution	1920 x 1080
Aspect Ratio	16:9
Max Color	16.2M
Brightness	Typical 400 Nits*
Contrast Ratio	Typical 800:1
Pixel Pitch	0.17925 x 0.17925mm
Viewing Angle	Horizontal 178°, Vertical 178°
Response rate	25ms (Typical On / Off)
Backlight	LED
Operating Temperature range	0 to 50°C (+ 50°C as panel surface temperature)

19.5" Diagonal Wide Aspect, Projective Capacitive, Anti-glare, Anti-smudge, UWVA, VA Display, with discrete Projective Capacitive Touch

Touch Technology	Projected Capacitive Touchscreen
Resolution	1920 x 1080
Aspect Ratio	16:9
Max Color	16.7M
Brightness	Typical 450 Nits*
Contrast Ratio	Typical 3000:1
Pixel Pitch	0.2265 x 0.2210mm
Viewing Angle	Horizontal 170°, Vertical 170°
Response rate	25ms (Typical On / Off)
Backlight	LED
Operating Temperature range	0 to 50°C (+ 50°C as panel surface temperature)

23.8" Diagonal Wide Aspect, Projective Capacitive, Anti-glare, Anti-smudge, IPS Display with discrete Projective Capacitive Touch

Touch Technology	Projected Capacitive Touchscreen
Resolution	1920 x 1080
Aspect Ratio	16:9
Max Color	16.7M
Brightness	Typical 625 Nits*
Contrast Ratio	1000:1
Pixel Pitch	274.5 um x 2274.5 um
Viewing Angle	Horizontal 178°, Vertical 178°
Response rate	14ms (Typical On / Off)
Backlight	LED
Operating Temperature range	0 to 50°C (+ 50°C as panel surface temperature)

*NOTE: Nits is the measure of the typical brightness of the panel as specified, prior to anti-glare coating

*NOTES:

Technical Specifications

Portrait Display. With a Portrait Head Unit, the pre-OS environment will be displayed 90° in Landscape. Once the Windows OS loads, then the display will show Portrait.

*All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Technical Specifications-Graphics

Intel® HD Graphics (integrated)

Integrated Graphics

- Intel®UHDGraphics770 (integrated on 14th gen Core i7/ i5)
- Intel®UHDGraphics730 (integrated on 14th gen Core i3)
- Intel®UHDGraphics 710 (integrated on G Series Celeron®G6900TE)

DisplayPort

DisplayPort over the optional USB-C® module

Memory

The actual amount of maximum graphics memory can be >6GB. System memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (DVMT), to provide an optimal balance between graphics and system memory use.

Maximum Graphic Memory

Windows 10 >6 GB

Maximum Color Depth

- 64bits/ pixel
- 10th Generation Intel®Core™ processors:
 - Next Generation Intel®Clear Video Technology HDSupport is a collection of video playback and enhancement features that improve the end user's viewing experience
 - Encode/ transcode HDcontent
 - Playback of high-definition content including Blu-ray Disc
 - Superior image quality with sharper, more colorful images

Graphics/Video API Support

- DirectX Video Acceleration (DXVA) support for accelerating video processing o Full AVC/VC1/MPEG2/HEVC HW Decode
- Advanced Scheduler 2.0, 1.0
- Windows 11, Linux OS Support
- DirectX 12.1
- OpenGL 4.4
- Open CL 1.2 (Intel® HD Graphics 730)
- Open CL 1.2/2.0 (Intel® HD Graphics 710)

NOTE: the actual amount of maximum graphics memory can be less than the amounts listed above depending upon your computer's configuration.

Supported Display Resolutions and Refresh Rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate
640x480	60Hz640x48067Hz
640x480	72Hz
640x480	75Hz
720x400	70Hz
800x600	60Hz

Technical Specifications-Graphics

800x600	75Hz
1024x768	60Hz
1024x768	75Hz
1280x960	60Hz
1280x720	60Hz
1280x1024	60Hz
1280x1024	75Hz
1440x900	60Hz
1440x900	75Hz
1680x1050	60Hz
1920x1080	60Hz
3440x1440	60Hz 3440x144030Hz
2048x1536	60Hz
4096x2160	60Hz
4096x2160	60Hz

Technical Specifications-Memory

MEMORY**Type**

DDR5-5600 SODIMM (transfer rates up to 5600 MT/s)

Maximum

64 GB

of Slots

2 SODIMM

Memory Upgrades

- RAM8GB (1x8GB) DDR5 5600
- RAM8GB (1x8GB) DDR5 5600 PRC
- RAM16GB (1x16GB) DDR5 5600
- RAM16GB (2x8GB) DDR5 5600
- RAM16GB (1x16GB) DDR5 5600 PRC
- RAM16GB (2x8GB) DDR5 5600 PRC
- RAM32GB (1x32GB) DDR5 5600
- RAM32GB (2x16GB) DDR5 5600
- RAM32GB (1x32GB) DDR5 5600 PRC
- RAM32GB (2x16GB) DDR5 5600 PRC
- RAM64GB (2x32GB) DDR5 5600

NOTE: Memory speed 5600 MT/ s can be achieved via two SODIMMs per channel (2DPC) when populated with the same part number.

For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system. Memory modules support data transfer rates up to 2400 MT/s; actual data rate is determined by the system's configured processor. See processor specifications for supported memory data rate.

CAUTION: You must shut down the Retail System and disconnect the power cord before adding or removing memory modules. Regardless of the power-on state, voltage is always supplied to the memory modules as long as the Retail System is plugged in to an active AC outlet. Adding or removing memory modules while voltage is present may cause irreparable damage to the memory modules or system board.

Technical Specifications-Storage

SOLID STATE STORAGE**Drive Bays :** (2) M.2 PCIe x4 2280/2230 Combo (for storage)**PCIe NVMe Solid State Drives (SSD)¹**

- SSD 256GB 2280 PCIe NVMe Value
- 256GB PCIe 2280 NVMe Self Encrypted OPAL2 Value Solid State Drive
- SSD 512GB 2280 PCIe NVMe Value
- SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell
- SSD 1TB 2280 PCIe NVMe Value
- SSD 1TB 2280 PCIe-4x4 NVMe Three Layer Cell
- SSD 2TB 2280 PCIe-4x4 NVMe Three Layer Cell
- 4TB PCIe-4x4 2280 NVMe Three Layer Cell double-sided M.2 Solid State Drive

Storage accelerator

- NVMe RAID 1

Notes:

1. Storage DriveLock does not work with Self-Encrypting or Optane based storage

NOTE: For hard drives and solid state drives, GB= 1 billion bytes. TB= 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

SSD 256G2280 PCIe NVMe Value

Capacity	256GB
Interface	PCIe NVMe
Form Factor	M.2
Height	2.38mm
Width	22mm
Length	80mm
Weight	<10g
Maximum Sequential Read	2000 MB/s ±20%
Maximum Sequential Write	900 MB/s ±20%
Logical Blocks	500,118,192
Operating Temperature	0° to 70°C (32° to 158°F) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

256GB PCIe 2280 NVMe Self Encrypted OPAL2 Value Solid State Drive

Capacity	256GB
Interface	PCIe NVMe
Form Factor	M.2
Height	2.38mm
Width	22mm

Technical Specifications-Storage

Length	80mm
Weight	<10g
Maximum Sequential Read	2000 MB/s \pm 20%
Maximum Sequential Write	900 MB/s \pm 20%
Logical Blocks	500,118,192
Operating Temperature	0° to 70°C (32° to 158°F) [ambient temp]
Features	TCG Opal 2.0; TRIM; L1.2

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

512 GB M.2 2280 PCIe NVMe Three Layer Cell Value SSD

SSD 512 GB 2280 PCIe NVMe Value

Capacity	512GB
Interface	PCIe NVMe
Form Factor	M.2
Height	2.38mm
Width	22mm
Length	80mm
Weight	<10g
Maximum Sequential Read	2200 MB/s \pm 20%
Maximum Sequential Write	1000 MB/s \pm 20%
Logical Blocks	1,000,215,215
Operating Temperature	0° to 70°C (32° to 158°F) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell

Capacity	512GB
Interface	PCIe NVMe
Form Factor	M.2
Height	2.38mm
Width	22mm
Length	80mm
Weight	<10g
Maximum Sequential Read	6400 MB/s \pm 20%
Maximum Sequential Write	3500 MB/s \pm 20%
Logical Blocks	1,000,215,215
Operating Temperature	0° to 70°C (32° to 158°F) [ambient temp]

Technical Specifications-Storage

Features

Pyrite 2.0; TRIM; L1.2

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

SSD 1TB 2280 PCIe NVMe Value

Capacity	1TB
Interface	PCIe NVMe
Form Factor	M.2
Height	2.38mm
Width	22mm
Length	80mm
Weight	<10g
Maximum Sequential Read	2200 MB/s \pm 20%
Maximum Sequential Write	1600 MB/s \pm 20%
Logical Blocks	2,000,409,264
Operating Temperature	0° to 70°C (32° to 158°F) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

SSD 1TB 2280 PCIe-4x4 NVMe Three Layer Cell

Capacity	1TB
Interface	PCIe NVMe
Form Factor	M.2
Height	2.38mm
Width	22mm
Length	80mm
Weight	<10g
Maximum Sequential Read	6400 MB/s \pm 20%
Maximum Sequential Write	5000 MB/s \pm 20%
Logical Blocks	2,000,409,264
Operating Temperature	0° to 70°C (32° to 158°F) [ambient temp]
Features	APST; ASPM L1.2; NVME spec 1.2

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

SSD 2TB 2280 PCIe-4x4 NVMe Three Layer Cell

Capacity	2TB
----------	-----

Technical Specifications-Storage

Interface	PCIe NVMe
Form Factor	M.2
Height	2.38mm
Width	22mm
Length	80mm
Weight	<10g
Maximum Sequential Read	6400 MB/s \pm 20%
Maximum Sequential Write	5000 MB/s \pm 20%
Logical Blocks	4,000,797,360
Operating Temperature	0° to 70°C (32° to 158°F) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

4TB PCIe-4x4 2280 NVMe Three Layer Cell double-sided M.2 Solid State Drive

Capacity	4TB
Interface	PCIe NVMe
Form Factor	M.2
Height	2.38mm
Width	22mm
Length	80mm
Weight	<10g
Maximum Sequential Read	6400 MB/s \pm 20%
Maximum Sequential Write	5000 MB/s \pm 20%
Logical Blocks	8,001,594,720
Operating Temperature	0° to 70°C(32° to 158°F) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

4TB 2280 PCIe-3x4 NVMe TLC Solid State Drive

Unformat ted Capacity	4TB
Interface	PCIe Gen 3
Form Factor	M.2

Technical Specifications-Storage

Height	2.38mm
Width	22mm
Length	80mm
Weight	<10g
Maximum Sequential Read	Up to 6600MB/s
Maximum Sequential Write	Up to 5200MB/s
Logical Blocks	2,000,409,264
Operating Temperature	0° to 70°C(32° to 158°F) [ambient temp]

NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

Technical Specifications – Networking and Communications

Networking/Communications

Ethernet (RJ-45)

- Intel® I219-LM Gigabit Network Connection LOM (standard)
- Realtek RTL8153CH

Wireless

- Intel® Wi-Fi 7 BE200 and Bluetooth® 5.4 wireless card, vPro®;*
- Intel® Wi-Fi 7 BE200 and Bluetooth® 5.4 wireless card, non-vPro® **
- Intel Wi-Fi 6E AX211 Wi-Fi 6E and Bluetooth® 5.3 wireless card, non-vPro®***

Notes:

NIC Fundamentals:

By default, the HP BIOS set the HUB WOL setting to disabled state, which will not allow wake signal from the USB bus to initiate a wake event. On Engage One Plus, the Embedded Lan Controller is enabled by default and is what HP recommend using as the primary nic for WOL capability as seen in the BIOS F10 menu. If customer has a reason to use the HUB NIC and wants to wake the system from that NIC. They must enable wake events for the HUB to get the functionality.

*Wireless access point and Internet service required and not included. Availability of public wireless access points limited. The specifications for the 802.11ax WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the PC to communicate with 802.11ax WLAN devices. Wi-Fi 6 requires a wireless router, sold separately, that supports 802.11ax (Wi-Fi 6). Only available in countries where 802.11ax is supported.

** Wi-Fi 6 is backwards compatible with prior 802.11 specs.

You require a wireless access point and internet service. Limited public wireless access points are available. The specifications for the 802.11 WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it might affect the ability of the notebook to communicate with other 802.11 WLAN devices.

Intel® i219LM 10/100/1000 Integrated NIC	
Connector	RJ-45
System Interface	PCI (Intel proprietary) + SMBus
Data rates supported	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
IEEE Compliance	IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet)
Performance	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling (Hash Mode Only) Jumbo Frame 9K

Technical Specifications – Networking and Communications

Power consumption	Cable Disconnection: 25mW 100Mbps Full Run: 450mW 1000bp Full Run: 1000mW WoL Enable(S3/S4/S5): 50mW WoL Disable(S3/S4/S5): 25mW
Power Management	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
Management Interface	Auto MDI/MDIX Crossover cable detection
IT Manageability	Wake-on-LAN from modem standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
Security & Manageability	Intel®vPro® support with appropriate Intel®chipset components
Intel Wi-Fi 6 AX201 + BT5 (802.11ax 2x2, vPro, supporting gigabit file transfer speeds)non-vPro	
Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
Interoperability	Features Wi-Fi 6 technology
Frequency Band	802.11b/g/n/ax • 2.402 – 2.482 GHz 802.11 ^a /n/ac/ax • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz
Data Rates	• 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, ,80MHz & 160MHz) • 802.11ax : MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, ,80MHz & 160MHz)

Technical Specifications – Networking and Communications

Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM	
Security³	<ul style="list-style-type: none"> • IEEE compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • WAPI 	
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)	
Roaming	IEEE 802.11 compliant roaming between access points	
Output Power²	<ul style="list-style-type: none"> • 802.11b : +18.5dBm minimum • 802.11g : +17.5dBm minimum • 802.11a : +18.5dBm minimum • 802.11n HT20(2.4GHz) : +15.5dBm minimum • 802.11n HT40(2.4GHz) : +14.5dBm minimum • 802.11n HT20(5GHz) : +15.5dBm minimum • 802.11n HT40(5GHz) : +14.5dBm minimum <ul style="list-style-type: none"> • 802.11ac VHT80(5GHz) : +11.5dBm minimum • 802.11ac VHT160(5GHz) : +11.5dBm minimum 	
Power Consumption	<ul style="list-style-type: none"> • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby: 10mW • Radio disabled: 8 mW 	
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity³	<ul style="list-style-type: none"> • 802.11b, 1Mbps : -93.5dBm 31áximum • 802.11b, 11Mbps : -84dBm 31áximum <ul style="list-style-type: none"> • 802.11a/g, 6Mbps : -86dBm maximum • 802.11a/g, 54Mbps : -72dBm maximum • 802.11n, MCS07 : -67dBm maximum • 802.11n, MCS15 : -64dBm maximum • 802.11ac, MCS0 : -84dBm maximum • 802.11ac, MCS9 : -59dBm maximum • 802.11ax, MCS11(HT40) : -59dBm maximum • 802.11ax, MCS11(VHT160) : -58.5dBm maximum 	
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications	
Form Factor	PCI-Express M.2 MiniCard with CNVi Interface	
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm	
Weight	1. Type 2230 : 2.8g 2. Type 126: 1.3g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F (–10° to 70° C)
	Non-operating	–40° to 176° F (–40° to 80° C)

Technical Specifications – Networking and Communications

Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF; LED White – Radio ON	
HP Integrated Module with Bluetooth® 4.0/4.1/4.2/5.0/5.1 Wireless Technology		
Bluetooth® Specification	4.0/4.1/4.2/5.0/5.1 Compliant	
Frequency Band	2402 to 2480 MHz	
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)	
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps	
	BLE : 1 Mbps data rate; throughput up to 0.2 Mbps	
	Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels.	
	Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)	
Transmit Power	The Bluetooth® component shall operate as a Class II Bluetooth®device with a maximum transmit power of +9.5 dBm for BR and EDR.	
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW	
Bluetooth® Software Supported Link Topology	Microsoft Windows Bluetooth® Software	
Power Management	Microsoft Windows ACPI, and USB Bus Support	
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249	
Bluetooth Profiles Supported	BT4.1-ESR 5/ 6/ 7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging &Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/ Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAXProfile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)	

Technical Specifications – Networking and Communications

Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)
Realtek RTL8822CE 802.11ac 2x2 Wi-Fi + BT5	
Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
Interoperability	Wi-Fi®certified
Frequency Band	802.11b/g/n • 2.402 – 2.482 GHz 802.11a/n/ac • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz
Data Rates	• 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, & 80MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security3	<ul style="list-style-type: none"> IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/ b/ g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification IEEE 802.11i <ul style="list-style-type: none"> WAPI
Network Architecture Models	Ad-hoc (Peer to Peer)

Technical Specifications – Networking and Communications

	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> 802.11b : +18.5dBm minimum 802.11g : +17.5dBm minimum 802.11^a : +18.5dBm minimum 802.11n HT20(2.4GHz) : +15.5dBm minimum 802.11n HT40(2.4GHz) : +14.5dBm minimum 802.11n HT20(5GHz) : +15.5dBm minimum 802.11n HT40(5GHz) : +14.5dBm minimum <ul style="list-style-type: none"> 802.11ac VHT80(5GHz) : +11.5dBm maximum 802.11ac VHT160(5GHz) : +11.5dBm minimum
Intel Wi-Fi 6 AX201 + BT5 (802.11ax 2x2, non-vPro, supporting gigabit file transfer speeds) non-vPro	
Wireless LAN Standards	IEEE802.11a IEEE802.11b IEEE802.11g IEEE802.11n IEEE802.11ac IEEE802.11ax IEEE802.11d IEEE802.11e IEEE802.11h IEEE802.11i IEEE802.11k IEEE802.11r IEEE802.11v
Interoperability	Features Wi-Fi 6 technology
Frequency Band	802.11b/g/n/ax • 2.402 – 2.482 GHz 802.11 ^a /n/ac/ax • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz 5.825 – 5.850 GHz
Data Rates	<ul style="list-style-type: none"> 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS0 ~ MCS15, (20MHz, and 40MHz) 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz) 802.11ax: MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)
Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
Security³	<ul style="list-style-type: none"> IEEE compliant 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification IEEE 802.11i <ul style="list-style-type: none"> WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points

Technical Specifications – Networking and Communications

Output Power²	<ul style="list-style-type: none"> • 802.11b : +18.5dBm minimum • 802.11g : +17.5dBm minimum • 802.11^a : +18.5dBm minimum • 802.11n HT20(2.4GHz) : +15.5dBm minimum • 802.11n HT40(2.4GHz) : +14.5dBm minimum • 802.11n HT20(5GHz) : +15.5dBm minimum • 802.11n HT40(5GHz) : +14.5dBm minimum <ul style="list-style-type: none"> • 802.11ac VHT80(5GHz) : +11.5dBm minimum • 802.11ac VHT160(5GHz) : +11.5dBm minimum • 802.11axHT40(2.4GHz) : +10dBm minimum • 802.11axVHT160(5GHz) : +10dBm minimum 	
Power Consumption	<ul style="list-style-type: none"> • Transmit mode 2.0 W • Receive mode 1.6 W • Idle mode (PSP)180 mW(WLANAssociated) • Idle mode 50 mW(WLANunassociated) • Connected Standby 10mW • Radio disabled 8 mW 	
Power Management	ACPIand PCIExpress compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity³	<ul style="list-style-type: none"> • 802.11b, 1Mbps : -93.5dBm 33áximum • 802.11b, 11Mbps : -84dBm 33áximum <ul style="list-style-type: none"> • 802.11a/g, 6Mbps : -86dBm maximum • 802.11a/g, 54Mbps : -72dBm maximum • 802.11n, MCS07 : -67dBm maximum • 802.11n, MCS15 : -64dBm maximum • 802.11ac, MCS0 : -84dBm maximum <ul style="list-style-type: none"> • 802.11ac, MCS9 : -59dBm maximum • 802.11ax, MCS11(HT40) : -59dBm maximum • 802.11ax, MCS11(VHT160) : -58.5dBm maximum 	
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure	
	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMOcommunications and Bluetooth communications	
Form Factor	PCI-Express M.2 MiniCard with CNViInterface	
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216 : 1.67 x 12.0 x 16.0 mm	
Weight	1. Type 2230 : 2.8g 2. Type 126 : 1.3g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F(–10° to 70° C)
	Non-operating	–40° to 176° F(–40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)

Technical Specifications – Networking and Communications

LED Activity	LED Amber – Radio OFF; LED Off – Radio ON
HP Integrated Module with Bluetooth® 4.0/ 4.1/ 4.2/ 5.0/ 5.1 Wireless Technology	
Bluetooth® Specification	4.0/4.1/4.2/5.0/5.1 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps
	BLE : 1 Mbps data rate; throughput up to 0.2 Mbps
	Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels.
Transmit Power	The Bluetooth® component shall operate as a Class II Bluetooth® device with a maximum transmit power of +9.5 dBm for BR and EDR.
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
Bluetooth® Software Supported Link Topology	Microsoft Windows Bluetooth® Software
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC60950 UL, CSA, and CE Mark
Bluetooth Profiles Supported	BT4.1-ESR5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 – Link Layer Privacy LE Privacy 1.2 – Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP) 2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)
Realtek RTL8822CE 802.11ac 2x2 Wi-Fi + BT5	
Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
Interoperability	Wi-Fi® certified
Frequency Band	802.11b/g/n • 2.402 – 2.482 GHz 802.11a/n/ac • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz

Technical Specifications – Networking and Communications

	<ul style="list-style-type: none"> • 5.47 – 5.725 GHz 5.825 – 5.850 GHz
Data Rates	<ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS0 ~ MCS15, (20MHz, and 40MHz) 802.11ac: MCS0~MCS9, (1SS, and 2SS) (20MHz, 40MHz & 80MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security³	<ul style="list-style-type: none"> • IEEE and Wi-Fi compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11^a: +18.5dBm minimum • 802.11n HT20 (2.4GHz): +15.5dBm minimum • 802.11n HT40 (2.4GHz): +14.5dBm minimum • 802.11n HT20 (5GHz): +15.5dBm minimum • 802.11n HT40 (5GHz): +14.5dBm minimum • 802.11ac VHT80 (5GHz): +11.5dBm 35áximum • 802.11ac VHT160 (5GHz): +11.5dBm minimum
Power Consumption	<ul style="list-style-type: none"> • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity³	802.11b, 1Mbps: -93.5dBm 35áximum 802.11b, 11Mbps: -84dBm 35áximum 802.11 ^a /g, 6Mbps: -86dBm 35áximum 802.11 ^a /g, 54Mbps: -72dBm 35áximum 802.11n, MCS07: -67dBm 35áximum 802.11n, MCS15: -64dBm 35áximum 802.11ac, MCS0: -84dBm 35áximum • 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard with CNVi interface
Dimensions	3. Type 2230: 2.3 x 22.0 x 30.0 mm 4. Type 1216: 1.67 x 12.0 x 16.0 mm

Technical Specifications – Networking and Communications

Weight	3. Type 2230 : 2.8g 4. Type 126: 1.3g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating Non-operating	14° to 158° F(–10° to 70° C) –40° to 176° F(–40° to 80° C)
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
LEDActivity	LEDAmber – Radio OFF;LEDOff – Radio ON	
HP Integrated Module with Bluetooth® 4.0/ 4.1/ 4.2/ 5.0 Wireless Technology		
Bluetooth® Specification	4.0/4.1/4.2/5.0 Compliant	
Frequency Band	2402 to 2480 MHz	
Number of Available Channels	Legacy : 0~79 (1 MHz/CH)BLE:0~39 (2 MHz/CH)	
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connect ion Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/ 177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)	
Transmit Power	The Bluetooth® component shall operate as a Class IIBluetooth® device with a maximum transmit power of +4 dBm for BBrand EDR.	
Power Consumpt ion	Peak (Tx) 330 mWPeak (Rx) 230 mW Selective Suspend 17 mW	
Bluetooth® Software Supported Link Topology	Microsoft Windows Bluetooth® Software	
Power Management	Microsoft Windows ACPI, and USBBus Support	
Certificat ions	FCC(47 CFR)Part 15C,Section 15.247 &15.249	
Power Management Certifications	ETS300 328, ETS300 826	
	LowVoltage Directive IEC950 UL,CSA,and CEMark	
Bluetooth Profiles Supported	BT4.1-ESR5/6/7 Compliance LELink Layer Ping LEDual Mode LELink Layer LELow Duty Cycle Directed Advertising LEL2CAPConnection Oriented Channels Train Nudging &Interlaced Scan BT4.2 ESR08 Compliance LESecure Connection- Basic/Full LEPrivacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LEData Packet Length Extension FAXProfile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)	

Intel® Wi-Fi 7 BE200 and Bluetooth® 5.4 wireless card, vPro® and NonvPro Module

Technical Specifications – Networking and Communications

The Intel® Wi-Fi 7 BE200 adapter is designed to support the upcoming IEEE 802.11be standard – Wi-Fi 7 technology and the Wi-Fi Alliance Wi-Fi 7 certification. Aligned with the upcoming IEEE 802.11be standard, the Intel® Wi-Fi 7 BE200 module supports these key features: 4096QAM and 320MHz channels resulting in 2.4X higher peak data rates⁴, Multi-link Operation (MLO - eMLSR), Multi-resource unit (Multi-RU) and Puncturing.

Intel® Wi-Fi 7 BE200 Module Technical Specifications

GENERAL

Dimensions (H x W x D)	M.2 2230: 22mm x 30mm x 2.42mm (max) M.2 1216: 12mm x 16mm x 1.7 (+/-0.1) mm
Weight	M.2 2230: 3.07+/-0.15g M.2 1216: 0.75+/-0.04g
Radio ON/OFF Control	Supported
Connector Interface	M.2: PCIe*, USB
Operating Temperature (Ambient)	0°C to +50°C
Humidity Non-Operating	50% to 90% RH non-condensing (at temperatures of 25°C to 35°C)
Operating Systems	Microsoft* Windows 11*, Microsoft* Windows 10*, Linux*
Wi-Fi Alliance ⁶	Wi-Fi 7 Technology support, Wi-Fi CERTIFIED* 6 with Wi-Fi 6E, Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM*-Power Save, WPA3*, PMF*, Wi-Fi Direct*, Wi-Fi Agile Multiband*, Wi-Fi Location R2 HW readiness ⁷
IEEE WLAN Standard	IEEE 802.11-2020 and select amendments (selected feature coverage) IEEE 802.11a, b, d, e, g, h, i, k, n, r, u, v, w, ac, ax, be; Fine Timing Measurement based on 802.11-2016, 802.11az HW readiness
Bluetooth®	Bluetooth® 5.4 (Ant. 1)

SECURITY FEATURES

Security Methods	WPA3* personal and enterprise including WPA2* transition mode
Authentication Protocols	802.1X EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0 -MSCHAPv2 (EAP-SIM, EAP-AKA, EAP-AKA')
Encryption	128-bit AES-CCMP, 256-bit AES-GCMP

COMPLIANCE

Regulatory	For a list of country approvals, please contact your local Intel representatives.
US Government	FIPS ⁹ 140-3
Product Safety	UL, C-UL, CB (62368-1)

Product Name	Model Number	Version
Intel® Wi-Fi 7 BE200	BE200NGW BE200D2W	Wi-Fi 7, 2x2, Bluetooth® 5.4, M.2 2230 Wi-Fi 7, 2x2, Bluetooth® 5.4, M.2 1216

¹ Wi-Fi 7 (802.11be) WFA certification is not yet available. Intel® Wi-Fi 7 BE200 module will be delivered as a pre-certified solution.

² Name and features might change based on Bluetooth SIG direction

³ "5 Gbps Wi-Fi 7 2x2 client speed" - is based on the current draft of the 802.11be specification, which specifies the theoretical maximum data rate for a 2x2 device that supports 320 MHz channels in the 6GHz band, with a 4096 QAM modulation is 5.76 Gbps. Based on an industry-standard efficiency assumption, the resulting estimated maximum over-the-air 2x2 client UDP throughput speed would be 5 Gbps

⁴ "2.4X higher peak data rates" Intel® Wi-Fi, 7 BE200 claims, are based on the comparison of the expected maximum theoretical data rates for similarly configured single radio Wi-Fi 7 (802.11be) and standard Wi-Fi 6 (802.11ax) Wi-Fi solutions as documented in current IEEE 802.11be spec and IEEE

802.11 wireless standard specifications, and require the use of similarly configured 802.11be wireless network routers.

Technical Specifications – Networking and Communications

⁵ Intel® vPro® Technology is sophisticated and requires setup and activation. Availability of features and results will depend upon the setup and configuration of your hardware, software, and IT environment. To learn more, visit: <http://www.intel.com/technology/vpro>.

⁶ Support of Wi-Fi Alliance certifications is OS-dependent.

⁷ IEEE 802.11az hardware readiness per expected Wi-Fi Location R2 feature support and based on draft 2.1 of the IEEE802.11az amendment and is subject to change.

⁸ Some security solutions may not be supported by your device operating system and/or by your device manufacturer or may require additional hardware (e.g., UICC – SIM card). Check with your device manufacturer for details on availability.

⁹ Pre-certified

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc., and any use of such marks by Intel Corporation is under license.

Tests document the performance of components on a particular test, in specific systems. Differences in hardware, software, or configuration will affect actual performance. Consult other sources of information to evaluate performance as you consider your purchase. For more complete information about performance and benchmark results, visit www.intel.com/benchmarks.

Estimated results were obtained prior to implementation of recent software patches and firmware updates intended to address exploits referred to as "Spectre" and "Meltdown". Implementation of these updates may make these results inapplicable to your device or system.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document.

Intel disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit <http://www.intel.com/wireless>.

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction.

This device has not been authorized as required by the rules of the Federal Communications Commission. This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained.

Intel, the Intel logo, are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

* Other names and brands may be claimed as the property of others.

2024 Copyright © Intel Corporation. All rights reserved.

NFC NXP NPC300

Dimensions (L x W x H)	17 x 10 x 2.0 mm
Chipset	NPC300
System interface	I2C
NFC RF standards	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
NFC Forum Support	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2
Reader (PCD-VCD) Mode(1)	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz cards
Card Emulation (PICC-VICC) Mode(1)	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
Frequency	13.56 MHz
NFC Modes Supported	Reader/Writer, Peer-to-Peer
Raw RF Data Rates	106, 212, 424, 848 kbps

Technical Specifications – Networking and Communications

Operating temperature	0°C to 70°C		
Storage temperature	-20°C to 125°C		
Humidity	10-90% operating 5-95% non-operating		
Supply Operating voltage	4.35 to 5.25 Volts		
I/O Voltage	1.8V or 3.3V		
Power Consumption	Booster enable, VCC_BOOST = 5V) Mode Power Consumption, Typical	VBAT= 3.3V, Polling	Detected Test Tag Type 1
			7.3 mA
		Detected Test Tag Type 2	Total 283.8 mA Net Module 236.8 mA
		Detected Test Tag Type 3	Total 288.8 mA Net Module 241.8 mA
		Detected Test Tag Type 4	Total 287.7 mA Net Module 240.7 mA
			Total 282.3 mA Net Module 235.3 mA
Antenna	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.		

Technical Specifications – Audio/Multimedia

High-Definition Audio

Engage One System Audio (Realtek ALC3247-CG)

Type	Integrated
HD Stereo Codec	High-Definition Audio codec
Internal Speaker Amplifier	4-channel DAC, 4-channel ADC, and an integrated stereo Class-D Speaker Amplifier
Sampling	Sampling frequency=48kHz
Analog Audio	Yes, Audio Jack support CTIA type
# of Channels on line-out	Stereo (Left & Right channels)
Internal speaker	Yes
Microphone	Yes, stereo digital microphone input with Realtek proprietary Acoustic Echo Cancellation (AEC), Beam Forming (BF), and Noise Suppression (NS) technology, significantly improving voice quality for PC VoIP applications
Maximum Power Output	2W per channel at 5V power supply
Headphone	yes

Technical Specifications – Integrated Camera

1.2 Basic Specification

Camera	5MP+IR camera
Sensor	RGB : 1/4.7" 5M CMOS (OV05C) IR : 1/10.5" 400x400 CMOS (OV6211)
Effective Pixel	RGB : 2880x1800 IR : 400x400
Output Image Size	RGB : Up to 2880x1800 IR : Up to 400x400
Output Format	YUY2, MJPEG
Frame Rate	RGB : 30fps @ MJPG 5M IR : 30fps @Y8 400x400
Lens Structure	RGB : F/2.0, 4P IR : F/2.0, 3P
Outside Dimension	96±0.2 x 5±0.1 x 3.38±0.15 (unit: mm) (Including Lens + PCB + adhesive tape)
PCB thickness	0.3±0.08mm
Interface	USB 2.0
LED Color	White

Technical Specifications – Integrated Camera

RGB: HP 5MP Camera

IR: HP IR Camera

Features

- Automatic image control
- ✓ Automatic / Manually Exposure Control
- ✓ Automatic / Manually White Balance Control
- ✓ Automatic Gain Control
- ✓ Face AE
- ✓ Temporal Noise Reduction
- ✓ High Dynamic Range
- ✓ Human Presence Detection
- ✓ Low Light Compensation
- ✓ Power Line Flicker Compensation (default@ 60Hz)
- ✓ Gain
- Resolution Support for Still/Motion Image
- Image Quality Control (Adjust Manually)
- ✓ Brightness
- ✓ Contrast
- ✓ Hue
- ✓ Saturation
- ✓ Sharpness
- ✓ Gamma
- ✓ Backlight Compensation


Technical Specifications – Power

POWER

Power Supply	280Watt Smart PFC Standard Barrel 7.4mm Straight 1.8m C14 SR-S; 89% efficiency (advance hub) 230Watt Smart PFC Slim Barrel 7.4mm Right Angle ; 89% efficiency (Column hub & VESA hub) 150 Watt Smart PFC Slim Barrel 7.4mm Straight , 89% efficiency (hubless)
Operating Voltage Range	90V~265VAC
Rated Voltage Range	100V~240AC
Rated Line Frequency	50~60HZ
Operating Line Frequency Range	47~63HZ
Rated Input Current	<2.4A RMS/280W, <3.52A/230W
Power Supply Fan	N/A
ENERGY STAR® Compliant	ENERGY STAR® certified configurations available and EPEAT® registered *
Power Cord Length	1.8m
NOTE: Power supply meets ENERGY STAR® compliance in conjunction with a select range of processors and modules. *Energy Star in under testing & in process of certification at the time this document is written	

WEIGHTS & DIMENSIONS

NOTE: Weight and dimensions below do not include MSR, Biometric Reader, Webcam, or CFD.




Head Unit-15.6"		
	Metric	US
Head Unit-15.6" Dimensions (Landscape)		
Height [mm/in]	241.0	9.5
Width [mm/in]	397.6	15.7
Depth [mm/in]	26.4	1.0
Volume (Litters/cubic inches)	2.5	152.04
Head Unit-15.6" Dimensions (Portrait)		
Height [mm/in]	391.6	15.4
Width [mm/in]	241.0	9.5

Technical Specifications – Power


Depth [mm/in]	26.4	1.0
Volume (Liters/cubic inches)	2.5	152.04
Head Unit-15.6" Weight (Landscape)		
[kg/lb.]	3.37	7.4
Head Unit-15.6" Weight (Portrait)		
[kg/lb.]	3.37	7.4

Technical Specifications – Measurement




Head Unit-15.6"		
	Metric	US
Landscape dimensions (when working angle is 12 degree)		
Height [mm/in]	365.8	14.4
Width [mm/in]	391.6	15.4
Depth [mm/in]	220.0	8.7
Volume (Litres/cubic inches)	31.5	1923.13
Portrait dimensions (when working angle is 12 degree)		
Height [mm/in]	439.4	17.3
Width [mm/in]	305.0	12.0
Depth [mm/in]	220.0	8.7
Volume (Litters/cubic inches)	29.5	1799.21
Head Unit-15.6" Weight (Landscape) + Gordo Stand		
[kg/lb.]	6.70	14.8
Head Unit-15.6" Weight (Portrait)+ Gordo Stand		
[kg/lb.]	6.70	14.8

Technical Specifications – Measurement





Head Unit-15.6"		
	Metric	US
Landscape dimensions (when working angle is 40~140 degree)		
Height [mm/in]	346.3	13.6
Width [mm/in]	391.6	15.4
Depth [mm/in]	220.0	8.7
Volume (Litters/cubic inches)	29.8	1820.61
Portrait dimensions (when working angle is 40~140 degree)		
Height [mm/in]	404.0	15.9
Width [mm/in]	305.0	12.0
Depth [mm/in]	271.8	10.7
Volume (Litters/cubic inches)	33.5	2043.76
Head Unit-15.6" Weight (Landscape)+ Gordo Stand		
[kg/lb.]	6.70	14.8
Head Unit-15.6" Weight (Portrait)+ Gordo Stand		
[kg/lb.]	6.70	14.8

Technical Specifications – Measurement




Head Unit-19.5"		
	Metric	US
Head Unit-19.5" Dimensions (Landscape)		
Height [mm/in]	292.6	11.5
Width [mm/in]	494.8	19.2
Depth [mm/in]	29.4	1.2
Volume (Litres/cubic inches)	4.2	256.60
Head Unit-19.5" Dimensions (Portrait)		
Height [mm/in]	488.8	19.2
Width [mm/in]	292.6	11.5
Depth [mm/in]	29.4	1.2
Volume (Litres/cubic inches)	4.2	256.60
Head Unit-19.5" Weight (Landscape)		
[kg/lb.]	5.70	12.6
Head Unit-19.5" Weight (Portrait)		
[kg/lb]	5.70	12.6

Technical Specifications – Measurement




Head Unit-19.5"		
	Metric	US
Landscape dimensions (when working angle is 12 degree)		
Height [mm/in]	391.6	15.4
Width [mm/in]	488.8	19.2
Depth [mm/in]	220.0	8.7
Volume (Litres/cubic inches)	42.1	2569.78
Portrait 19.5" does not support 12 degrees		
Height [mm/in]		
Width [mm/in]		
Depth [mm/in]		
Volume (Litres/cubic inches)		
Head Unit-19.5" Weight (Landscape)		
[kg/lb.]	8.80	19.4
Head Unit-19.5" Weight (Portrait)		
[kg/lb]		

Technical Specifications – Measurement



Head Unit-19.5"		
	Metric	US
Landscape dimensions (when working angle is 40~140 degree)		
Height [mm/in]	368.0	14.5
Width [mm/in]	488.8	19.2
Depth [mm/in]	239.5	9.4
Volume (Litres/cubic inches)	43.1	2628.96
portrait dimensions (when working angle is 40~140 degree)		
Height [mm/in]	443.2	17.4
Width [mm/in]	305.0	12.0
Depth [mm/in]	336.5	13.2
Volume (Litres/cubic inches)	45.5	2775.77
Head Unit-19.5" Weight (Landscape)+Gordo Stand		
[kg/lb.]	8.80	19.4
Head Unit-19.5" Weight (Portrait)+Gordo Stand		
[kg/lb]	8.80	19.4



Technical Specifications – Measurement



Head Unit-23.8"		
	Metric	US
Head Unit-23.8" Dimensions (Landscape)		
Height [mm/in]	339.9	13.4
Width [mm/in]	570.4	22.5
Depth [mm/in]	29.4	1.2
Volume (Litres/cubic inches)	5.7	347.84
Head Unit-23.8" Dimensions (Portrait)		
Height [mm/in]	570.4	22.5
Width [mm/in]	339.9	13.4
Depth [mm/in]	29.4	1.2
Volume (Litres/cubic inches)	5.7	347.84
Head Unit-23.8" Weight (Landscape)		
[kg/lb.]	10.60	23.4
Head Unit-23.8" Weight (Portrait)		



Technical Specifications – Measurement

[kg/lb]	10.60	23.4
---------	-------	------



Head Unit-23.8"		
	Metric	US
Landscape dimensions (when working angle is 12 degree)		
Height [mm/in]	414.7	16.3
Width [mm/in]	570.4	22.5
Depth [mm/in]	220.0	8.7
Volume (Litres/cubic inches)	52.0	3175.67
Portrait 23.8" does not support 12 degrees		
Height [mm/in]		
Width [mm/in]		
Depth [mm/in]		
Volume (Litres/cubic inches)		
Head Unit-19.5" Weight (Landscape)		
[kg/lb.]	10.60	23.4
Head Unit-19.5" Weight (Portrait)		
[kg/lb]		

Technical Specifications – Measurement



Head Unit-23.8"		
	Metric	US
Landscape dimensions (when working angle is 40~140 degree)		
Height [mm/in]	386.2	15.2
Width [mm/in]	570.4	22.5
Depth [mm/in]	254.7	10.0
Volume (Litres/cubic inches)	56.1	3423.89
Portrait does not support 40~140 degree		
Height [mm/in]		
Width [mm/in]		
Depth [mm/in]		
Volume (Litres/cubic inches)		
Head Unit-19.5" Weight (Landscape)+ Gordo Stand		
[kg/lb.]	10.60	23.4
Head Unit-19.5" Weight (Portrait)+ Gordo Stand		
[kg/lb]		

Technical Specifications – Measurement

Pro Stand



Advanced Stand



Marketing Name	Pro Stand		Advanced Stand	
	Metric	US	Metric	US
Stand Dimensions(with Stability Base)				
Height [mm/in]	207.05	8.15	243.3	9.6
Width [mm/in]	305	12	305	12
Depth [mm/in]	220	8.7	220	8.7
Stand Dimensions (without Stability Base)				
Height [mm/in]	195.35	7.69	231.5	9.1
Width [mm/in]	105	4.13	110	4.3
Depth [mm/in]	105	4.13	110	4.3
Stand Weight with Stability Base				
Weight [kg/lb]	2.35	5.2	3.1	6.8
Stand Weight without Stability Base				
Weight [kg/lb]	0.95	2.1	1.7	3.7

Technical Specifications – Measurement

Engage One Pro G2 Advanced Fanless hub		
	Metric	US
Hub Dimensions (with Lifted Hub surround)		
Height [mm/in]	220.3	8.7
Width [mm/in]	305.3	12.0
Depth [mm/in]	36.7	1.4
Hub Dimensions (Without Lifted Hub surround)		
Height [mm/in]	100.0	3.9
Width [mm/in]	275.0	10.8
Depth [mm/in]	28.5	1.1
Hub Weight with Lifted Hub surround		
Weight [kg/lb]	1.00	2.2
Hub Weight (without Spring Hub surround) or Possum Hub Only		
Weight [kg/lb]	0.69	1.5

Engage One Pro G2 Advanced Fanless hub		
	Metric	US
Hub Dimensions (with U-shape Hub surround)		
Height [mm/in]	220.3	8.7
Width [mm/in]	305.3	12.0
Depth [mm/in]	36.7	1.4
Hub Dimensions (Without U-shape Hub surround)		
Height [mm/in]	100.0	3.9
Width [mm/in]	275.0	10.8
Depth [mm/in]	28.5	1.1
Hub Weight with Normal Hub surround		
Weight [kg/lb]	1.00	2.2
Hub Weight (without Spring Hub surround) or Possum Hub Only		
Weight [kg/lb]	0.69	1.5

Technical Specifications – Measurement

HP Engage One Pro G2 VESAhub and Hubless USB-A		
	Metric	US
Dimensions		
Height [mm/in]	150.0	5.9
Width [mm/in]	125.0	4.9
Depth [mm/in]	24.4	1.0
Weight(Without Adapter)		
[kg/lb.]	0.54	1.20

HP Engage One Pro G2 Slim VESAMount		
	Metric	US
Dimensions		
Height [mm/in]	120.0	4.7
Width [mm/in]	120.0	4.7
Depth [mm/in]	10.5	0.4
Weight		
[kg/lb.]	0.23	0.51

Engage Pro G2 Advanced Stand		
	Metric	US
Stand Dimensions(with Stability Base)		
Height [mm/in]	243.3	9.6
Width [mm/in]	305.0	12.0
Depth [mm/in]	220.0	8.7
Stand Dimensions (without Stability Base)		
Height [mm/in]	231.5	9.1
Width [mm/in]	110.0	4.3
Depth [mm/in]	110.0	4.3
Stand Weight with Stability Base (without wombat)		
Weight [kg/lb]	3.13	6.9
Stand Weight without Stability Base (without wombat)		

Technical Specifications – Measurement

Weight [kg/lb]	1.70	3.7
----------------	------	-----

Engage Pro G2 Stand		
	Metric	US
Stand Dimensions(with Stability Base)		
Height [mm/in]	239.3	9.0
Width [mm/in]	308.0	13.0
Depth [mm/in]	220.0	8.7
Stand Dimensions (without Stability Base)		
Height [mm/in]	239.3	9.0
Width [mm/in]	110.0	4.3
Depth [mm/in]	110.0	4.3
Stand Weight with Stability Base (without wombat)		
Weight [kg/lb]	3.13	6.9
Stand Weight without Stability Base (without wombat)		
Weight [kg/lb]	0.91	2

Technical Specifications - Miscellaneous Features

System Summary Dimension Matrix Summary table

Display Heads Only	Width (Horizontal)	Height (Vertical)	Thickness
15.6 Landscape	397.6	241.0	26.4
19.5 Landscape	494.8	292.6	29.4
23.8 Landscape	576.4	339.9	29.4
15.6 Portrait	241.0	391.6	26.4
19.5 Portrait	292.6	488.8	29.4
23.8 Portrait- Slim VESA only*	339.9	570.4	29.4

NOTE: *23.8" Portrait can only be support with SLIM VESA mount, not configurable with any Column stand, not configurable with column hub

	Width	Depth	Thickness
Stability Base Only	305.0	220.0	11.7
Stability Base With Advance Hub	305.0	220.0	38.7
Delta Height with Advance hub (Note 1 – Add 27 mm to height dimensions when using with the Advance Hub)	305.0	220.0	27.0

10" CFD module		
	Metric	US
10" CFD Dimensions		
Height [mm/in]	170.2	6.7
Width [mm/in]	246.2	9.7
Depth [mm/in]	18.0	0.7
Weight(Without cable) [kg/lb]	1.00	2.20

Technical Specifications - Miscellaneous Features

MISCELLANEOUS FEATURES

Management Features

- Advanced Configuration and Power Management Interface (ACPI). Allows the system to wake from a low power mode.
- Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.
- Intel® Wired for Management support; industry wide initiative to make Intel® architecture based PCs, servers and mobile computers more inherently manageable out-of-the-box and over the network
- Dual State Power Button; acts as both an on/off button and a suspend-to-sleep button

HP Point of Sale Diagnostics UEFI:

- This utility enables hardware level testing outside the operating system on many components. The diagnostics can be invoked by pressing F2 at POST, and is available as a download from HP Support

Serviceability Features:

- System/Emergency ROM
- Flash ROM
- Flash Recovery with Video Configuration Record Software
- Over-Temp Warning on Screen (Requires IM Agents)
- Clear Password Jumper
- Clear CMOS Button
- Color coordinated cables and connectors
- Front power switch
- System memory can be upgraded without removing the system board or any internal components

Interpreting System Validation Diagnostic Front Panel LEDs and Audible Codes

During the system validation phase that occurs at system startup, the BIOS validates the functionality of the following subsystems and conditions:

- AC adapter
- System board power
- Processor failure
- BIOS corruption
- Memory failure
- Graphics failure
- System board failure
- BIOS authentication failure

If an error is detected, specific patterns of long and short blinks, accompanied by long and short beeps (where applicable) are used to identify the error. These patterns 48esi make up a two part code:

- Major – the category of the error
- Minor – the specific error within the category

 **NOTE:** Single beep/blink codes are not used.

Number of long beeps/blinks	Error category
1	Not used
2	BIOS

Technical Specifications - Miscellaneous Features

3	Hardware
4	Thermal
5	System board

Patterns of blink/beep codes are determined by using the following parameters:

- 1 second pause occurs after the last major blink.
- 2 second pause occurs after the last minor blink.
- Beep error code sequences occur for the first 5 iterations of the pattern and then stop.
- Blink error code sequences continue until the computer is unplugged or the power button is pressed.



NOTE: Not all diagnostic lights and audible codes are available on all models.

The red LED blinks to represent the major error category (long blinks). The white LED blinks to represent the minor error category (short blinks). For example, '3.5' indicates 3 long red blinks and 5 short white blinks to communicate the processor is not detected.

Category	Major/minor code	Description
BIOS	2.2	The main area (DXE) of BIOS has become corrupted and there is no recovery binary image available.
	2.3	The embedded controller policy requires the user to enter a key sequence.
	2.4	The embedded controller is checking or recovering the boot block.
	2.4	The embedded controller is checking or recovering the boot block.
Hardware	3.2	The embedded controller has timed out waiting for BIOS to return from memory initialization.
	3.3	The embedded controller has timed out waiting for BIOS to return from graphics initialization.
	3.4	The system board displays a power failure (crowbar).*
	3.5	The processor is not detected.*
	3.6	The processor does not support an enabled feature.
Thermal	4.2	A processor over temperature condition has been detected.*
	4.3	An ambient temperature over temperature condition has been detected.
	4.4	An MXM over temperature condition has been detected.
System board	5.2	The embedded controller cannot find valid firmware.
	5.3	The embedded controller has timed out waiting for the BIOS.
	5.4	The embedded controller has timed out waiting for BIOS to return from system board initialization.
	5.5	The embedded controller rebooted the system after a possible lockup condition had been detected through the use of a System Health Timer, Automated System Recovery Timer, or other mechanism.

* Indicates hardware triggered event; all other events are controlled by the BIOS.

TEMPERATURE, HUMIDITY, ALTITUDE

Temperature

Operating

50° to 104° F (10 to 40° C)

Technical Specifications - Miscellaneous Features

Humidity	Non-operating	-22° to 149° F (-30°to 65° C)
	Operating	20%-85% relative humidity at max inlet temperature
Shock	Non Operating	20%-85% relative humidity at max inlet temperature
	Operating	40g, six surfaces
Vibration	Non Operating	30g, six surfaces
	Operating	2-g peak acceleration
Altitude (unpressurized)	Non Operating	3-g peak acceleration
	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 30,000 ft (9,144 m)

Technical Specifications - Environmental

ENVIRONMENTAL & INDUSTRY

Environmental Data

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR® certified configurations available
- EPEAT® Gold with Climate+ registered configurations available. See www.epeat.net for registration status and tier levels by country.

*Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit www.epeat.net for more information

Sustainable Impact Specifications

- 15% Recycle SGCC steel chassis, 80% Recycled Aluminum in rear plate
- 75% post-consumer recycled plastic in packaging⁴
- Low halogen¹
- 25% Ocean-Bound Plastic in speaker enclosure²
- 50% Ocean-Bound Plastic in fan enclosure²
- 25% ITE-derived closed loop plastic⁶

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Engage One Pro model is based on a typically configured system featuring an SSD, a high efficiency power supply, and a Microsoft Windows® operating system.

HP Engage One Pro G2 AiO System Model 15.6"

Energy Consumption (in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	10.79W	10.87W	10.63W
Normal Operation (Long idle)	9.53 W	9.53W	9.41W
Sleep	1.77 W	1.76W	1.76W
Off	0.95W	0.96W	0.95W

Heat Dissipation*

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	42.89 BTU/hr	44.59 BTU/hr	43.02 BTU/hr
Normal Operation (Long idle)	36.54 BTU/hr	37.39 BTU/hr	36.74 BTU/hr
Sleep	11.15 BTU/hr	11.29 BTU/hr	11.12 BTU/hr
Off	3.92 BTU/hr	3.99 BTU/hr	3.92 BTU/hr

* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour

NOTE: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

HP Engage One Pro G2 AiO System Model 19.5"

Energy Consumption (in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	12.58W	13.07W	12.65 W

Technical Specifications - Environmental

Normal Operation (Long idle)	10.71 W	10.96W	10.79 W
Sleep	3.28 W	3.31W	3.26W
Off	1.15W	1.18 W	1.15 W
Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	42.89 BTU/hr	44.59 BTU/hr	43.02 BTU/hr
Normal Operation (Long idle)	36.54 BTU/hr	37.39 BTU/hr	36.74 BTU/hr
Sleep	11.15 BTU/hr	11.29 BTU/hr	11.12 BTU/hr
Off	3.92 BTU/hr	3.99 BTU/hr	3.92 BTU/hr

* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour

HP Engage One Pro G2 AiO System Model 23.8" **

Energy Consumption (in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	21.49W	21.55W	21.27W
Normal Operation (Long idle)	10.41W	10.52W	10.31W
Sleep	1.56W	1.55W	1.56W
Off	0.85W	0.86W	0.85W

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	42.89 BTU/hr	44.59 BTU/hr	43.02 BTU/hr
Normal Operation (Long idle)	36.54 BTU/hr	37.39 BTU/hr	36.74 BTU/hr
Sleep	11.15 BTU/hr	11.29 BTU/hr	11.12 BTU/hr
Off	3.92 BTU/hr	3.99 BTU/hr	3.92 BTU/hr

* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour

**TCO is only offered on the 23.8"

Technical Specifications - Environmental

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 2 memory slots
- M.2 2230 slot for WLAN
- (1) M.2 2280 slot for SSD

Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

Mercury greater than 1ppm by weight
Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive – 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680.1 (EPEAT) standard at the <Gold> level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 45.16% post-consumer recycled plastic (by wt.)
- This product is 96% recycle-able when properly disposed of at end of life.

Packaging Materials

External: PAPER/Corrugated

Internal: PLASTIC/Polyethylene Expanded – EPE

PLASTIC/Polyethylene low density – LDPE

The EPE foam packaging material is made from 100% recycled content.

The corrugated paper packaging materials contains at least 35% recycled content.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf>):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds

Technical Specifications - Environmental

- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Notes: * EPE foam packaging material is considered “recycled” pre-Consumer. The scrap or waste EPE material from the manufacturing process of these EPE foam pieces are re-introduced into the manufacturing process.

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

HP Inc. offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the HP Inc. web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

HP Inc. Corporate Environmental Information

For more information about HP's commitment to the environment

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www8.hp.com/us/en/hp-information/environment/ecolabels.html>

ISO 14001 certificates:

[PC Product Design ISO 14001 certificate](#)

and

[HP Operations ISO 14001 certificate](#)

Technical Specifications - Environmental

Footnotes

¹External power supplies, WWAN modules, power cords, cables and peripherals excluded.
Service parts obtained after purchase may not be Low Halogen.

²Percentage of ocean-bound plastic contained in each component varies by product

⁴Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.

⁶ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1-2018 standard.

HP Engage One After Market Option Matrix

HP Engage One Pro Advance Hubs & cable AMOs

AMO Part No.	Description
9YH40AA#xxx	HP Engage One Pro G2 Adv Fan-less Hub *
156N6AA#xxx	HP Engage One Pro G2 Adv Fan-less Hub White *
<i>*Included 280W PSU/1.8M cord, need one of the separate cable below</i>	
2Z8M9AA	HP Engage One Pro G2 2m USB-C® cable black
2Z8N0AA	HP Engage One Pro G2 0.5m USB-C® cable black
2Z8N2AA	HP Engage One Pro G2 2m USB-C® cable gray
2Z8N1AA	HP Engage One Pro G2 0.5m USB-C® cable gray
201A2AA	HP Engage One Pro G2 Column/ VESA hub to Advance hub 2m black
201A1AA	HP Engage One Pro G2 Column/ VESA hub to Advance hub 0.5m black
316D6AA	HP Engage One Pro G2 Column/ VESA hub to Ad hub 2m gray
316D7AA	HP Engage One Pro G2 Column/ VESA hub to Ad hub 0.5m gray

HP Engage One Pro G2 VESAHubs & cable AMOs

AMO Part No.	Description
9YH42AA#xxx	Engage One Pro VESAHub**
<i>**Included 230WPSU/ 1.8Mcord &cable</i>	
Additional Cable available to connect the Column hub or the VESA hub to the Advance hub below	
201A2AA	HP Engage One Pro G2 Column/VESA hub to Advance hub 2m black
201A1AA	HP Engage One Pro G2 Column/VESA hub to Advance hub 0.5m black
316D6AA	HP Engage One Pro G2 Column/VESA hub to Ad hub 2m gray
316D7AA	HP Engage One Pro G2 Column/VESA hub to Ad hub 0.5m gray

HP Engage One Pro G2 Mounting Option AMOs

AMO Part No.	Description
1A4E7AA	Engage One Pro Slim VESA
326R7AA	Engage One Pro Slim VESAWhite
9YH43AA	Engage One Pro U-shaped Adapter
156N7AA	Engage One Pro U-shaped Adapter White
1A4E5AA	HP Engage One Pro G2 AiOStability Plate
1A4E6AA	HP Engage One Pro G2 AiOStability Plate White

HP Engage One After Market Option Matrix

2W7M4AA	Engage One Pro Flexible Pole Single Mount
2W7M3AA	Engage One Pro Flexible Back-to-Back Bracket
9YH51AA	Engage One Pro Undercounter Mount

HP Engage One Pro G2 Mounting Option AMOs

AMO Part No.	Description
2W7M4AA	Engage One Pro Flexible Pole Single Mount
2W7M3AA	Engage One Pro Flexible Back-to-Back Bracket

HP Engage One Pro G2 Customer Facing Displays (CFDs)

AMO Part No.	Description
9YH48AA	HP Engage One Pro G2 6.6 inch Customer Facing Display
156N9AA	HP Engage One Pro G2 6.6 inch White Customer Facing Display
10P79AA	HP Engage 6.6 inch Pole Display
156N9AA	HP Engage 6.6 inch WPole Display
1XD80A#ABA, #ABT, #AC3	HP Engage One 10 Display
1XD81A#ABA, #ABT, #AC3	HP Engage One 10t Display
3FH66A#ABA, #ABT, #AC3	HP Engage One 10w Display
3FH67A#ABA, #ABT, #AC3	HP Engage One 10tw Display
20C49A#AB1, #AB2, #ABT, #AC3	HP Engage One 14 FHDMonitor
20C50A#AB1, #AB2, #ABT, #AC3	HP Engage One 14 FHDNo Stand Monitor
20C51A#AB1, #AB2, #ABT, #AC3	HP Engage One 14t FHDMonitor
20C52A#AB1, #AB2, #ABT, #AC3	HP Engage One 14t FHDNo Stand Monitor
2D9V5A#ABT, #AC3	HP Engage One 16t FHDMonitor
2D9X0A#ABT, #AC3	HP Engage One 16t FHDNo Stand Monitor
2D9Y5A#ABT, #AC3	HP Engage One 16ts FHDMonitor
2D9Z4AA#ABT, #AC3	HP Engage One 16ts FHDNo Stand Monitor

HP Engage One Pro G2 Customer Facing Displays (CFDs) Stands

AMO Part No.	Description
10P60AA	HP Engage 6 Clean Mount Arm Bracket

HP Engage One After Market Option Matrix

10P61AA	HP Engage 6 Stability Mount Arm Bracket
10P77AA	HP Engage 10 Clean Mount Stand
10P78AA	HP Engage 10 Stability Mount Stand
10P58AA	HP Engage 14 Clean Mount Stand
10P62AA	HP Engage 14 Stability Mount Stand

HP Integrated Peripherals AMOs

AMO Part No.	Description
9YH50AA	HP Engage One Pro G2 Fingerprint Reader
2U551AA	HP Engage One Pro G2 Magnetic Stripe Reader
2V9G4AA	HP Engage One Pro G2 White Magnetic Stripe Reader
9YH49AA#AB4, #ABA, #ABB	HP Engage One Pro G2 Bar Code Scanner

HP All-in-One Adjustable Height Stand

For Engage One Pro 23.8" All-in-One systems



HP Engage One After Market Option Matrix



Model

HP All-in-One Adjustable Height Stand Black
HP All-in-One Adjustable Height Stand White

518U6AA
518U7AA

Introduction

Optimize viewing of the Engage One Pro 23.8" All-in-One system with the HP All-in-One Adjustable Height Stand. Available in either black or white, this stand allows for height adjustment, tilt, and pan.

Key Features and Benefits

- Position All-in-One for maximum ergonomic comfort—promotes wellness in any work area
- Small footprint frees up your workspace and increases your efficiency
- Integrated base rollers enable 360° rotation of the stand so you can share your views with others
- Features technology that enables light touch adjustments without levers or knobs
- Five-inch (13 cm) height adjustment (landscape mode) ergonomically accommodates average range of users
- Easy to use—simple installation and effortless operation
- Everything is included to neatly route cables behind the stand, out of the way
- IEC 62368-1 certified

Compatibility

HP Engage One After Market Option Matrix

The HP All-in-One Adjustable Height Stands are compatible with the Engage One Pro 23.8" All-in-One system, both in portrait and landscape orientation, when an Engage One Pro VESA Mount or VESA Hub is configured on the system.

Requirements: The Engage One Pro VESA Mount or the Engage One Pro VESA Hub is required to mount the HP Engage One Pro G2 23.8" system onto the HP All-in-One Adjustable Height Stand. SKU options are listed below and are sold separately from the stand.

Drop-in-box SKUs (for configuration with HP Engage One Pro G2 system)

For black systems:

- HP Engage One Pro G2 AiO Slim VESA Mount (A30MJAV)
- HP Engage One Pro G2 AiO VESA Hub (A30MMAV)

For white systems:

- HP Engage One Pro G2 AiO Slim VESA Mount White (A30MKAV)
- HP Engage One Pro G2 AiO VESA Hub White (A30MNAV)

After-market option SKUs

For black systems:

- HP Engage One Pro G2 AiO Slim VESA Mount (1A4E7AA)
- HP Engage One Pro G2 AiO VESA Hub (9YH42AA)

For white systems:

- HP Engage One Pro G2 AiO Slim VESA Mount White (326R7AA)
- HP Engage One Pro G2 AiO VESA Hub White (326R6AA)

Certifications:

- IEC 62368-1:2014
- UL 62368-1, 2nd Ed. And CAN/CSA C22.2 No. 62368-1-14, 2nd Ed.

Compliant with:

- EN 62368-1:2014/ A11:2017
- BS EN 62368-1:2014/ A11:2017

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP.

General


Lift (Height Adjust) in Landscape Mode	5" (13 cm)
Lift (Height Adjust) in Portrait Mode	2.5" (6.4 cm)
Weight Capacity	16-36 lb (7.3-16.3 kg)
Monitor up/down tilt	Up to +25°/ -5° (depends on the height)
Pan	360°

Mechanical

Product Weight	13.8 lb (6.2 kg)
Product Dimensions	20.4" x 11.5" x 17.6" (51.8 cm x 29.2 cm x 44.8 cm)

HP Engage One After Market Option Matrix

Shipping Weight	17.4 lb (7.9 kg)
Shipping Dimensions	23" x 13" x 7.3" (58.5 cm x 33.0 cm x 18.5 cm)



Box Contents

Base, stand, monitor mounting bracket, screws, weight adjustment tool, cable ties, quick-setup manual

HP Engage 6.6 inch Customer Facing Display



Model

HP Engage 6.6 inch Customer Facing Display	9YH48AA
HP Engage 6.6 inch Customer Facing Display White	156N8AA

HP Engage One After Market Option Matrix

Introduction

Give customers a clear view of their transactions and sharing engaging, colorful, dynamic content at the point of sale with LCD touch display.

Key Benefits

- 6.6 inch diagonal compact LCD display that integrates easily into your retail solution.
- Position as need with adjustable height and swiveling of the display head.
- Place the durable, dust resistant display in a range of high traffic areas.
- A USB connector powers the display and eliminated the need for additional cabling.
- The edge to edge, bezel free 63 esign is easy to clean, helps protection from dust, and create a sleek, modern appearance.

Overview - After Market Options

Compatibility

The HP Engage 6.6 inch Customer Facing Display is compatible with HP Retail Point of Sale Systems.

NOTE: Not all Point of Sale system models are available in all regions.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP.

Overview - After Market Options

General	
Display Method	Backlit LED
Brightness	400 Nits
Resolution	1440 x 720
Pixel Pitch	0.105 x 0.105 mm
Active Area	75.6 (H) x 151.2 (V) mm
Contrast Ratio	1000:1 (max)
Response Rate	25 ms (rise+fall time)
Viewing Angle	Left: 85° Right: 85° Top: 85° Bottom: 85°
Color Gamut	70% (CIE 1931 Standard NTSC)
Mechanical	
Display Dimensions (WxHxD)	171.4 x 76.2 x 56.35 mm
Display Weight	0.25 kg
Hinge Adjustability	Rotation Range 0°~90° (normal using) Folded to 90° for shipping
Color	HP Black / White
Connection	
Interface	USB
Power	
Operating Voltage	5V
Full Load Current	6.5W (DC +5V, 1300mA)
Idle Current 0.64W	TBD
Temperature Range	
Operating	0°C to 35°C [32 to 95°F] at 10% to 90% humidity (non-condensing)
Non-operating	-30°C to 65°C [-22 to 149°F] at 0% to 95% humidity (38.7°C maximum wet bulb temperature)
Webcam	30fps USB 2.0 webcam, 5MP (2560x1920) resolution
NOTE: The Integrated webcam is a windows Hello Camera and IR is supported on 5MP Camera	
Operating System	
Compatible with:	Windows 11 Pro 64-bit Windows 10 Professional 64-bit) Windows 10 IoT Enterprise 2021 LTSC Windows 10 IoT Enterprise 2019 LTSC Android™ 11 Android™ 11 AOSP Android™ 11 GMS FreeDos 2.0 SUSE Linux® Enterprise Server 15
Kit Contents	
HP Engage 6.6 inch Customer Facing Display, documentation, warranty card.	

Overview - After Market Options

HP Engage One Pro G2 Integrated Barcode Scanner



Model

HP Engage One Pro G2 Integrated Barcode Scanner
Configure to Order (CTO) with HP Engage
HP Engage One Pro G2 Integrated Barcode Scanner
After-market option (AMO)

B3WY5AV (bottom), B3WY8AV
(left), B3WZ0AV (right)
B6BP1AA

Introduction

This integrated scanner streamlines your checkout area, while offering placement options, acceptance of various barcodes and coupons, and enhanced features for an easier, more accessible checkout experience.

Key Features and Benefits

- Enjoy a configurable, clutter-free scanning space. Our new integrated barcode scanner inserts into the left, right, or bottom of the HP Engage One Pro G1 AiO or HP Engage One Pro G2 AiO for a sleek, seamless look.
- Quickly scan mobile wallets and digital coupons from customer mobile devices or printed 1D and 2D barcodes, or validate customer identity with passport OCR.
- Enable both employees and customers alike to scan items with ease. The unit reads barcodes when they're placed within 1.2" to 18.5" *inches from the scanner.
- Minimize fatigue by adjusting the scan light for your ambient lighting conditions— lower the brightness in darker environments and increase in brighter environments.
- Choose to have the barcode scanner included when you purchase your HP Engage One Pro G2 AiO, or add it on later as you need the upgrade. **
- The HP Engage One Pro G2 AiO flip- sensing feature will turn off the LED when the head unit is flipped.
- Enjoy support for your retail operating system of choice. The HP Engage One Pro G2 Integrated Barcode Scanner supports Windows 11, Windows 10, Windows IoT, Linux®, and Android-based systems.
- Rest easy that your IT investment is supported by a three- year standard limited warranty.

*Min/max reading distance vary for different symbologies/densities.

**Optional feature sold separately or as an add-on feature.

Compatibility

Overview - After Market Options

The HP Engage One Pro G2 Integrated Scanner is compatible with the HP Engage One Pro All-in-One system and the HP Engage One Pro G2 All-in-One system.

NOTE: Not all Point of Sale systems are available in all regions.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP.

General		
Image Sensor	1200 x 800 CMOS	
Illumination Aimer	White LED	
	Red LED 625± 10nm	
Depth of Field	Typical Performance *	
	Symbologies	Depth of Field
	EAN-13	50mm-470mm (13mil)
	Code39	55mm-260mm (5mil)
	PDF-417	60mm-190mm (6.7mil)
	Data Matrix	43mm-240mm (10mil)
	QR Code	30mm-320mm (15mil)
Symbol Contrast	25% minimum reflectance	
Roll (tilt)	360°	
Pitch	±60°	
Skew	±60°	
Field of View	Horizontal 47°, Vertical 30°	
1D decode symbologies	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.	
	AIM 128	
	China Post 25	
	Codabar	
	Code 11	
	Code 39	
	Code 49	
	Code 93	
	Code 128	
	Code 16K	
	Coupon	
	EAN-8	
	EAN-13	
	Febraban	
	GS1-128 (UCC/EAN-128)	
	GS1 Composite (EAN UCC Composite)	
	GS1 Databar (RSS)	
	Industrial 25	
	Interleaved 2 of 5	
	ISBN	
	ISBT 128	
	ISSN	
	ITF-6	
	ITF-14	
	Matrix 25	
	MSI-Plessey	

Overview - After Market Options

	Plessey Standard 25 UPC-A UPC-E
2D decode symbologies	Aztec Code Chinese Sensible Code Code One Data Matrix GM Code MaxiCode MicroPDF417 Micro QR Code PDF417 QR Code
Postal decode symbologies	Australian Post KIX Post Royal Mail USPS Intelligent Mail USPS Planet USPS Postnet
OCR symbologies	Passport OCR
Mechanical	
Dimensions (W xD x H)	30.7 x 45.0 x 10.1 mm (Maximum)
Weight	9.6g
Color	Black
Interface/Connection	
Interface	USB
Temperature	
Operating	-20°C to 40°C (-4°F to 104°F)
Storage	-40°C to 70°F (-40°F to 158°F)
Humidity (non-condensing)	5% to 95%
Power	
Operating Voltage	5VDC±5%
Current at 5VDC	Operating: 300mA (RMS typical), 450mA (RMS max.) Idle: <50mA (level mode), <135mA (sense mode) Sleep: <1.5mA
Rated Power Consumption	1.5 W Typical
Drivers	Windows USB HID-KB and OPOS & JPOS (via USB-COM mode drivers)
Ambient Light	0- 100,000 lux
Water Penetration Protection	IP54
Operating System	
Compatible with:	Windows Windows 11 Windows 10 Pro 64bit Windows 10 IoT Enterprise 2016 LTSC 64bit (RS1) Windows 10 IoT Enterprise 2019 LTSC 64bit (RS5)
	Linux

Overview - After Market Options

Red Hat/CentOS 5.6.8 and above (64 bit)
Suse Linux Enterprise 11/12 SP3 and above (64 bit)
Ubuntu 12.04/14.04 LTS and above (64 bit)

Android

Android 8.0 and above

Agency Certifications

FCC Part15, Class B, CE EMC Class B, IEC62471, RoHS, IEC 62368-1, AfPS GS 2019, EK1-ITB 2000, UL, CNS13438

AMO Kit Contents

HP Engage One Pro G2 Integrated Barcode Scanner, documentation, warranty card

Overview - After Market Options

HP Engage One Magnetic Stripe Reader



Model	
HP Engage One Pro G2 Magnetic Stripe Reader	2U551AA
HP Engage One Pro G2 White Magnetic Stripe Reader	2V9G4AA

Compatibility

The HP Engage One Pro G2 Magnetic Stripe Reader is compatible with the HP Engage One Pro G2 All-in-One System.

NOTE: Not all Point of Sale system models are available in all regions.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP.

Overview - After Market Options

General

Magnetic stripe formats	ISO 7811, AAMVA
Card Thickness	0.38 to 1.14 mm (0.015 to 0.045 in)
Indicators	Bi-colored LED, beeper (requires system audio driver)
Card Speed	3 to 75 ips (7.6 to 190.5 cm/s)

Mechanical

Weight	5.67 g
Slot width	1.14 mm (0.045 in)
Color	HP Black HP White

Connection

Interface	Eight-pin male Molex 51021-0800
Cable Length	125 ± 6.4 mm

Power

Power Supply	3.0 to 3.6 VDC
I/O Voltage Range	2.7 to 3.6 VDC
Active Power Supply Current	5
mA Standby Power Supply Current	0.03 mA

Temperature Range

Operating	0°C to 55°C
Relative Humidity	-10% to 90% non-condensing

Reliability

Operating Life	1,000,000 card swipes minimum
----------------	-------------------------------

Agency Certifications

FCC, CE, USB-IF

Operating Systems

Compatible with:	Windows 11 Pro 64-bit Windows 10 Professional (64-bit) Windows 10 IoT Enterprise 2021 LTSC Windows 10 IoT Enterprise 2019 LTSC Android™ 11 Android™ 11 AOSP Android™ 11 GMS FreeDOS 2.0 SUSE Linux® Enterprise Server 15
------------------	--

Kit Contents

HP Engage One Pro G2 Magnetic Stripe Reader, documentation, warranty card.

Overview - After Market Options

HP Engage One Pro G2 Fingerprint Reader



Model

HP Engage One Pro G2 Fingerprint Reader

9YH50AA

Compatibility

The HP Engage One Pro G2 Fingerprint Reader is compatible with the HP Engage One Pro G2 All-in-One System.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP.

Overview - After Market Options

General

Sensor Type	Capacitive
Array Size	208 x 288 pixels
Image Resolution	508 DPI
Gray Scale	8-bit (256 levels)

Mechanical

Image Area	10.4 x 14.4 mm
Image/Coating	Steel Coat
Color	HP Black

Digital ID Reliability

NVM Storage	100 templates
Data Retention	20 years
Erase/Write	100,000 cycles

Interface/Connection

Interface	USB 2.0
Interface Connector	5 pin, 0.8mm pitch wire-type (gold-plated)

Temperature

Operating	-30° to +85°C
Storage	-40° to +85°C
Humidity (non-condensing)	5% to 85%
ESD Tolerance	IEC 61000-4-2 Level 4

Power

Consumption	Supply voltage: single supply voltage, 3.0V to 3.6V Imaging mode : 105 mA @ 3.3V Sleep mode : 1350 uA @ 3.3V
Wake-up Time	< 15 ms (Sleep to imaging)

Drivers

Windows USB HID-KB and OPOS & JPOS (via USB-COM mode drivers)

Operating Systems

Compatible with:	Windows 11 Pro 64-bit Windows 10 Professional (64-bit) Windows 10 IoT Enterprise 2021 LTSC Windows 10 IoT Enterprise 2019 LTSC Android™ 11 Android™ 11 AOSP Android™ 11 GMS FreeDOS 2.0 SUSE Linux® Enterprise Server 15
-------------------------	--

Agency Certifications

FCC (47 CFR) Part 15C, Section 15.247 & 15.249

Kit Contents

HP Engage One Pro G2 Fingerprint Reader, documentation, warranty card.

Overview - After Market Options

Service and Support

Ninety-day (90-90-90), one-year (1-1-1), and three-year (3-3-3) limited warranty delivers (ninety days/one year/three years) of on-site, next business day² service for parts and labor and complimentary limited technical support.³ Three-year onsite and labor are not available in all countries. Service offers terms up to 5 years by choosing an optional HP Care Pack.¹ To choose the right level of service for your HP product, visit HP Care Pack Central: <http://www.hp.com/go/cpc>

NOTES:

- 1. Terms and conditions may vary by country. Certain restrictions and exclusions apply. Other warranty variations may be offered in your region.
- 2. On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.
- 3. Technical support applies only to HP-configured Compaq and third-party HP-qualified hardware and software. 24 x 7 support may not be available in some countries.

Date of change:	Version History:		Description of change:
January 27, 2025	From v1 to v2	Changed	Format

Copyright © 2025 HP Development Company, L.P.

All rights reserved. Microsoft, Windows, Windows 7, Windows 8, and Windows 10 are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Intel®, Celeron®, Pentium® and Core™ are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Bluetooth® is a registered trademark of its proprietor and used by HP Inc. under license. ENERGY STAR® is a registered trademark owned by the U.S. Environmental Protection Agency.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.