#### **NEW** from

# GOODS

## **SAM45** SPT-360


### Stylish POS Terminal



- Energy Efficient
   Slim Display
   Sleek Chassis
   Small Footprint

- 15" LED LCD Display True-Flat PCAP Touch

- Easy Installation
   Fanless
   Microsoft Azure Certified



#### Ideal for Retail, Hospitality and Ticketing



**Optional MSR** 

- Energy Efficient and Low Heat Generation Architecture
- Slim Display, Sleek Chassis and Small Footprint Design
- 15' LED LCD Display with True-Flat PCAP Touch
- IP55 Dust and Waterproof Front Panel
- Superior Serviceability and Easy Installation
- Fanless Operation and No Ventilation Hole
- Microsoft Azure certified



Optional 10" Rear Display



Side View



Optional 2 x 20 Customer Display



**Rear View** 

Specifications	
CPU	Intel Bay Trail J1900 up to 2.42G Quad core (2M Cache)
Memory	DDRIIIL One slot. 4GB standard expandable to 8GB DDRIIIL expansion slots: mini PCle slot & m.2 Slot
Storage device(s)	In Australian Standard with 128 GB SSD, can also be purchased with a 500 GB SATA HDD (Special Order) or larger SSD Drives
Display	15" LED Backlight LCD Display
Resolution	1024 x 768
Tilt Angle	N/A
Touch Panel	True Flat PCAP Touch (Standard in Australia) Optional; 5 Wire Resistive touch (Special Order, MOQ Applies) USB I/F
I/O Ports	4 x RS-232 Ports (2 x DB9, 1 x RJ45) with 5V/12V BIOS selectable, one port selectable to RS422/485 6 x Standard USB Ports (2 x USB 2.0/2 x USB 3.0 on Bottom, 2 x USB 2.0 on the side) 1 x 10/100/1000Mb Ethernet Port. Half/Full duplex capability 1 x VGA Port for 2nd Display + 12V power outlet 1 x Parallel port (Factory Option) 1 x Cash Drawer Port (Controls 2 drawers with optional Y-cable) 12/24V selectable 1 x Audio Ports (Line out)
Audio	N/A
OS Support	POSReady 7 / WIN 8 Industry Retail / WIN IoT
Environmental Sealing	IP55 to Front
Operating Environment	0 ~ +40 °C, 20 ~ 85% RH with SSD
Storage Environment	-20 ~ +60 °C, 10 ~ 85% RH
Power Supply	DC 12V/5A
External Dimensions (WxDxH)	380mm x 380mm x 380mm
Weight	5.9 Kg

