

XT-1815P

15-inch Mountable Touch POS



Key Features

- 15-inch TFT LCD w/ True-Flat PCAP (G+G) and 5-wire Resistive Touch
- Intel Core™ i3-1215U - 10M Cache, up to 4.40 GHz
- Fanless cooling system for silent and efficient operation
- 8GB DDR4 RAM (2 x DDR4 SO-DIMM slots, 3200MTs, up to 64GB)
- 128GB M.2 SSD and PCIe*4
- VESA mount installation with seamless integration



Fanless & Slim Design



Rich I/O Interfaces



Angle Adjustable

Specifications

XT-1815P	
Processor	Intel® Core™ i3-1215U
System Memory	8GB DDR4 RAM (2 x DDR4 SO-DIMM slots, 3200MTs, up to 64GB)
Storage	128GB Easy access M.2 SSD (PCIe 4.0 x 4 NVMe / SATA)
LCD Panel	15-inch TFT LCD, 1024 x 768
Touch Panel	True-Flat Projected Capacitive Multi Touch True- Flat 5-wire Resistive Touch
Speaker	1 x 2W High Quality Speaker
I/O Interface	
USB	3 x USB 3.2 Type A 1 x USB 3.2 Type C (w/ DP) 3 x USB 2.0 Type A (On Side of Unit – 2 Left, 1 Right)
LAN	1 x RJ45 10/100/1000Mbps Giga Ethernet
COM	2 x COM (RJ45), w/ RI/5V/12V by BIOS 1 x COM (DB9), w/ RI/5V/12V by Jumper (Option)
VGA	1 x DB-15 VGA Port (Option)
HDMI	1 x HDMI Port
Audio	1 x Line-out/MIC-in
Cash Drawer	1 x RJ11 port supports 2 cash drawer, w/ 12V/24V by jumper
DC Power Out	1 x DC 12V Power Out (DC 2.1mm)
DC Power In	1 x Standard DIN 4pin type
Power Management	
Power Adapter	12V@7.5A, 90W Adapter
Mechanical & Environmental	
Dust and Water	IP65 on Front Bezel
Tilt Adjustment	0° ~ 90°
Dimensions	3551 (W) x 305.92 (H) x 45.7 (D) mm
Weight	4.65 kg
Certification	CE/FCC/LVD
Operating System	Windows 10/11
TPM	TPM2.0
Operating Conditions	0°C to +40°C / 20 to 80% without condensation
Storage Conditions	-20°C to +60°C / 20 to 85% without condensation
Optional Accessories	
2nd Display	9.7" (1024 x 768) LCD Display (Optional PCAP Touchscreen)
Customer Display	VFD and LCD Customer Display
MSR (Right Side)	Bi-directional, Comply with ISO 7811 and Three Track support
Wi-Fi (Left Side)	Wi-Fi IEEE 802.11 a/b/g/n/ac
NFC (Left Side)	RFID 13.56 MHz, Comply Mifare, ISO14443AB-4 and Felica
VESA Bracket	VESA-Compatible, 75 x 75 (mm)

Specifications subject to change without notice.